

	CHAINS	
13+27.8	<p>1/16 COR. 2-3.N.6. E.CEN. 1/16 of 2</p>	<p>S. 89° 35 1/2' W. thru the center of section 2. Set a 3/4" x 30" iron pin for the East 1/16 corner on the E. &amp; W. centerline of the section, with a 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.</p>
26+55.6	<p>1/4 COR. INTERIOR 2-3.N.6. CEN. 1/4 COR</p>	<p>Intersect the N. &amp; S. centerline of the section at Sta. 26+55.1, the temporary center of section. For the center of section we placed a concrete pedestal 12" square at top, 18" square at bottom and 36" high, set 30 inches in the ground, with a 2 1/2" brass cap on which is stamped a circle and the number 2 and, circumferentially, CEN. SEC. T. 3 N. R. 6 W.W.M. = O.S.H.D. We also set a 4" x 4" white guard post stenciled CENTER SEC. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black. No live trees available for bearing trees.</p>
39+73.8	<p>1/16 COR. 2-3.N.6. W.CEN. 1/16 of 2</p>	<p>Set a 3/4" x 30" iron pin for the West 1/16 corner on the E. &amp; W. centerline of section 2, with a 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.</p>
52+92.0	<p>1/16 COR. 2-3.N.6. N.W. 1/4 of 2</p>	<p>The quarter corner between sections 3 and 2, previously described.  Returning to the West 1/16 corner on the E. &amp; W. centerline of section 2, we ran  N. 0° 30' W. toward the center of the N.W. 1/4 of the section.</p>
13+16.8		<p>Set 3/4" x 30" iron pin for the center of the N.W. quarter of section 2, with a 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.</p> <p>Thence we ran S. 89° 44' W. toward the West boundary of the section.</p>
13+12.2	<p>1/16 COR. 2,3-3.N.6.</p>	<p>The North 1/16 corner on the line between sections 3 and 2, previously described. - 221 -  Returning to the South 1/16 corner on the line between sections 3 and 2, we ran,  N. 89° 36' E. between the North and South halves of the S. W. quarter of section 2.</p>
13+18.6	<p>1/16 COR. 2-3.N.6. S.W. 1/4 of 2</p>	<p>Set a 3/4" x 30" iron pin for the center of the S.W. 1/4 of the section, with 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.</p>
26+37.2		<p>The South 1/16 corner on the N. &amp; S. centerline of the section, previously described.  Thence N. 89° 31 1/2' E. between the North and South halves of the S.E. quarter of section 2.</p>
13+24.8	<p>1/16 COR. 2-3.N.6. S.E. 1/4 of sec. 2</p>	<p>Set a 3/4" x 30" iron pin for the center of the S.E. quarter of the section, with a 4" x 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.</p>
26+49.6	<p>SEC. COR. 4,3,2,10-3.N.6. S.W. COR. SEC. 3</p>	<p>The South 1/16 corner on the line between sections 2 and 1, previously described.  Returning to the corner to sections 33-34-3-4 on the Twp. line, we ran Southerly by traverse between sections 4 and 3. Not finding any trace of the quarter corner, we proceeded to the corner to sections 4-3-9-10, where we found a stone with 5 notches on the South and 3 notches on the East corners, also remnants of 3 bearing trees. Leaving the stone undisturbed, we set a 2" x 48" galv. iron pipe at a point 0.5 ft. North and 0.2 ft. East of the high point of the rock. The pipe has a brass cap on which is stamped a cross and the numbers 4-3-9-10 and, circumferentially, SEC. COR. T. 3 N. R. 6 W.W.M. = O.S.H.D. We also set a 4"x4" white guard post stenciled SEC. COR. on 2 faces in black, and marked 4 new bearing trees, as follows:</p>

Book I