

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 19, 20, 29 and 30,
Township 3 North, Range 6 West, W.M.,
Tillamook County, Oregon.

ORIGINAL

Stone, 16 x 14 x 12 in mound of stone, now only rock
scattered around point from which a:

- 60" Fir bears N83 $\frac{1}{2}$ °E 42 lks.; now 41" snag,
face and scribes burnt out.
- 50" Fir bears S57°E 28 lks.; now 37" stump,
cast of B scribe found.
- 50" Fir bears S40 $\frac{1}{2}$ °W 69 lks.; now 36" stump,
scribes TRT visible, rest burnt off.
- 36" Hemlock bears N20 $\frac{1}{2}$ °W 29 lks.; now 26",
down, roots in place, face and scribes
burnt off.

RESTORED

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked
"OREGON STATE BOARD OF FORESTRY T3N R6W S19 S20 S30 S29
1954 RE 2311," 32 inches in ground, in mound of stone
4'x3'x17", and from which a:

- 6" Fir bears S80°E 113.0 ft.; scribed T3N R6W
S29 BT RE 2311.
- 5" Fir bears N40°E 94.5 ft.; scribed T3N R6W
S20 BT.
- 52" Fir stump bears N36°W 99.0 ft.; scribed
T3N R6W S19 BT.
- 36" Fir stub 25' high bears S8°W 53.9 ft.;
scribed T3N R6W S30 BT.

Oregon State Board of Forestry metal location poster on
Original 50" Fir BT.
Also Poster on 36" Fir stub BT.
4" x 4" x 60" white Cedar post 2 ft. NW of pipe.

Dated March 18, 1954.

Restored by Richard Morris under my direction.
Richard Morris, Compassman



Present and witnessed by Robert Cowan, Lloyd Geraths, Alan Ramage

Book I