

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 17, 18, 19,
and 20, Township 13 South, Range 6 West, W.M.,
Tillamook and Washington Counties, Oregon.

ORIGINAL

Post, now missing, from which a:

- 48" Fir bears N13°E 112 lks.; now 55" snag,
face not exposed.
- 20" Fir bears S31½°E 86 lks.; now 30" stub 10 ft.
high, scribed 1S R S20 visible.
- 36" Fir bears S39°W 53 lks.; now 36" broken off
stub 8 ft. high, BT scribes remaining.
- 60" Fir bears N24°W 85 lks.; now 61" snag,
scribes TLS exposed.

RESTORED

Set 1½" x 36" Galvanized iron pipe with 3" bronze cap
marked "OREGON STATE BOARD OF FORESTRY TLS R6W S18
S17 S19 S20 1954 RE 2311," 35 inches in ground, in
notch in 30" fir log, in mound of stone, 1.5' x 2' x 6",
and from which a:

- 36" Fir snag bears N68°W 15.2 ft.; scribed
TLS R6W S18 BT.
- 24" Fir snag bears S23°W 15.5 ft.; scribed
TLS R6W S19 BT. Also old scribes BM 2145.01.
- 40" Fir snag bears S69°E 39.5 ft.; scribed
TLS R6W S20 BT RE 2311.
- 36" Fir stump bears N47°E 89.1 ft.; scribed
TLS R6W S17 B.

Oregon State Board of Forestry metal location poster on
24" Fir snag BT.
4" x 4" x 60" white Cedar post 1.5 ft. SE of pipe.

Dated March 23, 1954.

Restored by Richard Morris under my direction.
Richard Morris, Compassman



Present and witnessed by Robert Cowan, Lloyd Geraths
and Alan Ramage.