

HH

X

TILLAMOOK COUNTY

Thence N. 0° 42' W. on a true line between sections 3 and 2.

13+26.7 Set a 3/4"X 30" iron pin for the South 1/16 corner on the line between sections 3 and 2, with a 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

26+53.5 The quarter corner between sections 3 and 2, previously described.

Thence N. 0° 16' W., continuing on a true line between sections 3 and 2.

27+98.0 Centerline of the Wolf Creek highway at Sta. 1229+70.5 P.O.T.

39+73.1 Set 3/4"X 30" iron pin for the North 1/16 corner on the line between sections 3 and 2, with a 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

47+81.6 The corner to sections 34-35-3-2, on the line between townships 3 and 4 North, previously described.

From the corner to sections 2-1-11-12, we ran Westerly by traverse to the quarter corner between sections 2 and 11, where we found the scribed stump of one bearing tree. ~~xxxxx~~ For the quarter corner we set a 2"X 48" galv. iron pipe with brass cap on which is stamped a line with short cross mark and the numbers 2 and 11 and, circumferentially, 1/4 SEC. COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled 1/4 SEC. COR. on 2 faces in black, and marked 2 bearing trees, as follows:  
A 10" hemlock bears S. 30° E. 18.6 ft., scribed 1/4 S. B.T.  
An 18" hemlock bears N. 2° W. 19.8 ft., scribed 1/4 S. B.T.

This quarter corner is at a point 2643.2 ft. S. 89° 26 1/2' W. from the corner to sections 2-1-11-12, and also, 2635.7 ft. N. 89° 37' E. from the corner to sections 3-2-10-11.

Thence we ran N. 0° 42 1/2' W. thru the center of section 2.

13+27.6 Set a 3/4"X 30" iron pin for the South 1/16 corner on the N. & S. centerline of the section, with a 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H.D. PROP. COR. on other 2 faces in black.

26+55.1 Set temporary center of section.

47+49.7 The 1/4 corner between sections 35 and 2 on the Twp. line, previously described

Returning to the quarter corner between sections 2 and 1, we ran

S. 89° 35 1/2' W. thru the center of section 2.

13+27.8 Set a 3/4"X 30" iron pin for the East 1/16 corner on the E. & W. centerline of the section, with a 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

26+55.6 Intersect the N. & S. centerline of the section at Sta. 26+55.2, the temporary center of section. For the center of section we placed a concrete pedestal 12" square at top, 18" square at bottom and 36" high, set 30 inches in the ground, with a 2 1/2" brass cap on which is stamped a circle and the number 2 and, circumferentially, CEN. SEC. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled CENTER SEC. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black. No live trees available for bearing trees.