

TILLAMOOK COUNTY

A 20" fir bears S. 75° W. 61.4 ft., scribed T. 3 N. R. 6 W. S.9 B.T. This tree has old deep blaze on East near base and has been chopped into deeply on the North.

A 10" fir bears N. 55° W. 66.1 ft., scribed T. 3 N. R. 6 W. S.4 B.T.

A 4" fir bears N. 20° E. 19.7 ft., scribed T. 3 N. R. 6 W. S.3 B.T.

A 4" fir bears S. 65° E. 27.7 ft., scribed T. 3 N. R. 6 W. S.10 B.T.

Thence we ran N. 0° 26' W. on a true line between sections 4 and 3.

26+55.6

For the 1/4 corner on the line between sections 4 and 3, we set a 2"X 48" galv. iron pipe with brass cap on which is stamped a line with short cross mark and the numbers 4 and 3 and, circumferentially, 1/4 60R. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled 1/4 SEC. COR. on 2 faces and O.S.H.PROP. COR. on other 2 faces in black. No live trees available for bearing trees.

41+53.1

Centerline of the Wolf Creek highway at Sta. 1170+83.5 P.O.C.

47+25.0

The corner to sections 33-34-4-3 on the Twp. line, previously described.

Returning to the corner to sections 4-3-9-10, we ran Easterly by traverse to the quarter corner between sections 3 and 10. At a point 2660.8 ft. S. 89° 26' E. from the section corner, we found a heap of shattered stone with 1/4 cut in the face of one piece. We also found a dead 30" fir S. 24° 45' W. 15.2 ft. scribed 1/4 S. B.T., and a rotten stump N. 77° E. 15 ft. For the quarter corner we set a 2"X 48" galv. iron pipe with a ~~stamped~~ brass cap on which is stamped a line with short cross mark and the numbers 3 and 10 and, circumferentially, 1/4 SEC. COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We piled the fragments of stone around the pipe and set a 4"X 4" white guard post stenciled 1/4 SEC. COR. on 2 faces in black. No live trees available for bearing trees.

This corner lies 2649.3 ft. N. 89° 00' W. from the corner to sections 3-2-10 and 11.

Thence we ran N. 0° 13' W. thru the center of section 3.

13+22.3

Set 3/4"X 30" iron pin for the South 1/16 corner on the N.& S. centerline of the section, with 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

26+44.6

The temporary center of the section.

39+55.4

3/4"X 30" iron pin for the North 1/16 corner on the N.& S. centerline of section 3, with 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

47+22.9

The 1/4 corner between sections 34 and 3, previously described.

Returning to the quarter corner between sections 4 and 3, we ran

S. 89° 11 1/2' E. thru the center of section 3.

Book I

13+35.7

3/4"X 30" iron pin for the West 1/16 corner on the E.& W. centerline of section 3, with 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

181 26+71.3

Intersect the N.& S. centerline of the section at Sta. 26+446, the

181