CHAINS

## RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Center one-quarter corner in Section 30, T3S, R9W, W.M.; Tillamook County, Oregon.

ESTABLISHED 1887 (see county records)

30" Fir bears S62°W 60 lks. now 55" stump scribes \$\frac{1}{4}\$ S BT Visible.

30" Fir bears N62°E 92 lks. now missing (found remains of roots and large hole N62°W 92 lks.)

RESTORED

Var. 2120E

Set  $1\frac{1}{2}$ " X 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY  $0\frac{1}{4}$  S30 1957 RS 359," 35 inches in ground, in E-W fence line, and from which a:

l"x31" iron rod bears West 10.0 feet; 25" in ground and
 in E-W fence line.
l"x40" iron rod bears East 10.0 feet; 22" in ground and

1"x40" iron rod bears East 10.0 feet; 22" in ground and in E-W fence line.

Oregon StateBoard of Forestry metal location poster on fence post 3.6 ft. west. Set 4"x4"x60" white painted Cedar post 2 feet east of pipe.

Dated February 21, 1957

Restored by Albard Morris, Transitman under my direction.

REGISTERED OREGON LAND SURVEYOR

ARNOLD G. GIBSON

Present and witnessed by Lloyd Geraths Robert Sturm

Book I