CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 29, 30, 31 and 32 T. 3N, R. 6W, W.M., Tillamook and Washington Counties, Oregon.

ORIGINAL

Post (found down with scribes S32 R6W S29 visible) from which a:

48" Fir bears N26°E 20½ lks.; now 54" stump, faces unexposed.
60" Fir bears S31°E 21½ lks.; now 54" stump, faces unexposed.
40" Fir bears S38½°W 36 lks.; now 42" stump, faces unexposed.
30" Fir bears N8°45'W 69 lks.; now 33" hollow stump, portion of scribe visible on edge of burnt out face.

RESTORED

Var. 21 20E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "CREGON STATE BOARD OF FORESTRY T3N R6W S30 S29 S31 S32 1957 RS401," 33 inches in ground, in mound of stone, and from which a:

11" Fir bears N80°W 19.4 ft.; scribed T3N R6W S30 BT. 8" Fir bears N70°E 20.0 ft.; scribed T3N R6W S29 BT. 12" Fir bears S11°E 11.4 ft.; scribed T3N R6W S32 BT RS401. 9" Fir bears S14W 27.4 ft.; scribed T3N R6W S31 BT.

Set original post on NE edge of pipe.

Oregon State Board of Forestry metal location poster on 11" Fir BT.

Also poster on telephone pole on N. R/W of S.P.R.R. approx. 685' S.

Set 4" x 4" x 60" white painted Cedar post 1.0' NE of pipe.

Dated October 25, 1957

Restored by

REGISTERED OREGON LAND SURVEYOR

Richard A. Morris

401

Present and witnessed by Robert Sturm
Lloyd Geraths

Book I