## **CHAINS**

REESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY (See official plat)

One Quarter corner common to Sections 7 and 8, TLS, R7W, W.M., Tillamook County, Oregon.

## ORIGINAL

(No evidence of original corner found)

## REESTABLISHED

Var. 212E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S7 S8 1958 RS 401", 33 inches in ground, in mound of stone, and from which a:

29" Fir stump bears S40E 32.5 ft.; scribed 1/4 S8 BT RS401. 64" Fir stump bears N71W 134.5 ft.; scribed 1/4 S7 BT.

Oregon State Board of Forestry metal location poster on 64" Fir stump B.T Set 4" x 4" 72" white painted Cedar post 1.0' N.W. of pipe.

One Quarter corner common to Sections 7 and 18, T1S, R7W, W.M., Tillamook County, Oregon.

## REESTABLISHED

Var. 21 &E

Set 15" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S7 S18 1958 RS401", 33 inches in ground, and from which a:

58" Fir stump bears S79E 28.0 ft.; scribed 1/4 S18 BT RS401. 52" Fir stump bears N40W 26.1 ft.; scribed 1/4 S7 BT.

Oregon State Board of Forestry metal location poster on 58" Fir stump BT. Set 3" x 4" x 60" white painted Cedar post 1.2' S.W. of pipe.

Dated December 15, 1958

Reestablished by

REGISTERED
O R & G O N
LAND SURVEYOR

MAY 10. 1957
Richard A. Morris

Present and witnessed by R. Schulson

H. Russell

R. Cop

401

Book I

353