

CHAINS

REESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)

One Quarter corner common to Sections 1 and 12,
T1S, R8W, W.M., Tillamook County, Oregon.

ORIGINAL

(No evidence of original corner found)

REESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S1 S12 1958 RS401", 33 inches in ground, and from which a:

- 48" Fir snag bears S45 3/4 E 61.3 ft.; scribed 1/4 S12 BT RS401.
- 9" Alder bears N 63 1/4 E 32.5 ft.; scribed in bark, 1/4 S1 BT.

Oregon State Board of Forestry metal location poster on 48" Fir snag B.T.
Set 4" x 4" x 60" white painted Cedar post 1.0' S.W. of pipe.

Witness corner for corner common to Sections 1 and 12, T1S, R8W, W.M., Tillamook County, Oregon.

ORIGINAL

(No evidence of original witness corner found)

REESTABLISHED

Var. 21 $\frac{1}{2}$ E


At a point on the true range line S0°01' 50" W 33.0 ft. from the true corner point in the Wilson River (determined by call of original survey notes) set a 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY WC T1S R8W R7W S1 S7 S12 1958 RS401", 12 inches in ground, in mound of stone 24" high, and from which a:

- 10" Maple bears S71E 59.4 ft.; scribed X BT RS401.
- 2' x 3' rock face on lower edge of rock cliff bears N84W 7.4 ft.; scribed X B0.


Oregon State Board of Forestry metal location poster on 10" Maple BT.
Set 4" x 4" x 54" white painted Cedar post 0.5' S. of pipe.

Dated December 17, 1958.

Reestablished by



Richard A. Morris



Present and witnessed by R. Cop
R. Schulson
H. Russell