CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY (See official plat)

Southwest One Sixteenth corner for Section 30, T3S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21-1E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SW 1/16 S30 1958 RS401", 36 inches in ground, 1.3' S. of E & W fence, and from which a:

21 double Fir bears N52 2W 29.7 ft.; scribed SW 1/16 S30 BT. 22 Fir bears N39E 32.2 ft.; scribed SW 1/16 S30 BT RS 401.

Oregon State Board of Forestry metal location poster on 30" Fir N86W 13.5'
Set 4" x 4" x 72" white painted Cedar post 1.0' N.E. of pipe.

and the second of the second o

Northwest One Sixteenth corner for Section 30, T3S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY NW 1/16 S30 1958 RS401", 33 inches in ground, and from which a:

16 Fir bears S81E 26.1 ft.; scribed NW 1/16 S30 BT RS401.
12 Fir bears N35W 44.3 ft.; scribed NW 1/16 S30 BT.

Oregon State Board of Forestry metal location poster on 30" Alder N28W 5.0'.

Set $4^n \times 4^n \times 72^n$ white painted Cedar post 1.0 N.W. of pipe.

Dated December 15, 1958

Established by

REGISTERED
OREGON
LAND SURVEYOR

Richard A. Morris

Present and witnessed by L. Amort A. Gibson

Book I

364

EE4