

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)

Center-West-East One Sixty-fourth corner (SW corner of $E\frac{1}{2}$ of $SW\frac{1}{4}$ of $NE\frac{1}{4}$) for Section 27, T2S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. $21\frac{1}{2}^{\circ}E$

Set $1\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY C-W-E 1/64 S27 1959 RS401", 34 inches in ground, in small mound of stone, and from which a:

49" Cedar bears $N84\frac{1}{2}^{\circ}E$ 56.9 ft.; scribed C-W-E 1/64 S27 BT RS401.

33" Hemlock bears $N47^{\circ}W$ 110.2 ft.; scribed C-W-E 1/64 S27 BT.

Oregon State Board of Forestry metal location poster on 49" Cedar BT.

Set 4" x 4" x 55" white painted Cedar post 1.0' S.W. of pipe.

North One Sixteenth corner for Section 22 (East side), T2S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. $21\frac{1}{2}^{\circ}E$

Set $1\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N 1/16 S22 1959 RS401", 33 inches in ground, in mound of stone, and from which a:

22" Spruce bears $S57^{\circ}W$ 89.6 ft.; scribed N 1/16 S22 BT RS401.

Oregon State Board of Forestry metal location poster on 22" Spruce BT.


Set 4" x 4" x 56" white painted Cedar post 1.2'E of pipe.

Dated April 14, 1959

Established by



Richard A. Morris



Present and witnessed by H. Russell
R. Cop

N 1/16
22 4