

CHAINS

ESTABLISHED CORNERS FOR STATE OF OREGON-DEPARTMENT OF FORESTRY
 (See official plat)
 Center South One Sixteenth corner for Section 16, T3S, R8W,
 W.M., Tillamook County, Oregon.

CORRECTION REPORT

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S 1/16 C---C S16 1961 RS401", 33 inches in ground, and from which a:

- 10" Fir bears S13E 58.8 ft.; scribed CS 1/16 S16 BT RS401.
- 15" Fir bears S37½W 64.6 ft.; scribed CS 1/16 S16 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N.E. of corner pipe. Oregon State Forestry Department metal location poster on 10" Fir BT.

Present and witnessed by G. E. Nylund, A. Duncan

Northeast One Sixteenth corner for Section 16, T3S, R8W,
 W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY NE 1/16 S16 1961 RS401", 24 inches in ground, and from which a:

- 14" Cedar bears S18W 40.2 ft.; scribed NE 1/16 S16 BT RS401.
- 26" Cedar bears N60½E 58.3 ft.; scribed NE 1/16 S16 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N.W. of corner pipe. Oregon State Forestry Department metal location poster on 60" Cedar stump N51E 16.9'.

Corner pipe is on W. bank of 6" creek course S20E.

Present and witnessed by A. Duncan, E. Danielson

Dated January 22, 1962

Established by



Richard A. Morris
 MAY 10, 1957
 Richard A. Morris
 401

Can S. 76
 15-3-S.B.

N.W. 76
 16-3-S.B.