**CHAINS** 

ESTABLISHED CORNERS FOR STATE OF OREGON—DEPARTMENT OF FORESTRY (See official plat)

West One-sixteenth corner common to Sections 2 and 11, T3S, RIOW, W.M., Tillamook County, Oregon.

## ESTABLISHED

Var. 21/2E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "CREGON STATE BOARD OF FORESTRY W 1/16 S2 S11 1962 RS401", 34 inches in ground, and from which a:

26" Double Hemlock bears N22W 12.0 ft.; scribed W 1/16 S2 BT. 22" Hemlock bears S3E 6.3 ft.; scribed W 1/16 S11 BT RS401.

Set  $4^n \times 4^n \times 52^n$  white painted Cedar post 1.0 ft. SE of corner pipe. Oregon State Forestry Department metal location poster on 26" Double Hemlock BT.

Present and witnessed by D. Fletcher, C. Curl

\* \* \* \* \* \* \* \*

Northwest One-sixteenth corner for Section 11, T3S, R1OW, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 212E

Set 12" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY NW 1/16 S11 1962 RS401", 34 inches in ground, and from which a:

22" Hemlock bears N68W 17.3 ft.; scribed NW 1/16 Sll BT. 25" Hemlock bears S75E 16.7 ft.; scribed NW 1/16 Sll BT RS401.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. South of corner pipe. Oregon State Forestry Department metal location poster on 10" Hemlock North 2.0 ft.

Present and witnessed by D. Fletcher, C. Curl and D. Celschlager

Dated July 13, 1962

under my direction. Established by Harold Russell Engineer. Tech. I

> REGISTERED OREGON LAND SURVEYOR

Richard A. Morris

401

Book I

476