

5

(contd)

County Surveyor's Record, Tillamook County, Oregon

T4SR8W

Rewitnessed corners Leonard Whitmore, U.S. Forest Service, Hebo

1/4 cor. Set a fir limb for post
24 in. alder, N.74°W., 24 ft. mkd. 1/4 S78T (new BT)
7 8 18 in. alder, N.77°E., 20 ft. mkd., 1/4 S88T (new BT)

In the presence of Mervin Whitmore, Sept. 4, 1961
Hobart Means

T4SR10-11

12 7 Old original post lying upon the ground. Set dead pine limb
13 18 for corner.
8 in. pine, S.34°W., 12 ft. with location poster.
8 in. pine N, 1°E., 6 1/2 ft. with location poster.

In the presence of Derrill Derrick, Oct. 4, 1960

T4SR8-9W

12 7 Original post with rock mound at base.
13 18 20 in. fir, N.34°W., 19 ft. mkd. T4SR9WS12BT (new BT)
20 in. fir, N.53°E., 12 ft mkd. T4SR8WS7BT (new BT)
18 in. fir, S.39°E., 5 ft mkd. T4SR8WS18BT (new BT)
28 in. fir, S40°W., 40 ft. mkd. T4SR9WS13BT (new BT)

In the presence of Mervin Whitmore, Sept. 4, 1961
Hobart Means

1/16th corner.

T6SR10W

6 Proportioned E 1/16th corner between sections 6-7.
7 Set 1 in. pipe 2 ft. above ground.
14 in. hemlock, S.61°30'W., 53 ft. mkd. E. 1/16th S7BT (new BT)
32 in. sawed off fir stump N.7°E., 8 1/2 ft mkd. E. 1/16th S6BT (new BT)

In the presence of Derrill Derrick, Nov. 2, 1961

1/4 corner

T6SR10W

6 Set hemlock post alongside original post.
7 34 in. hemlock, S.17°E., 32 ft. mkd. 1/4 S7BT (new BT)
34 in. hemlock, N.88°W., 30 ft. mkd. 1/4 S7BT (new BT)

In the presence of Mervin Whitmore, Jan. 2, 1961
Don Jarmon

By - 5-4 5 - M. Whitmore