

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

South East One Sixteenth corner for Section 6,
T. 2N, R. 9W, W.M., Tillamook County, Oregon

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SE 1/16 S6 1958 RS401," 33 inches in ground, and from which a:

27" Hemlock bears N89½E 61.4 ft.; scribed SE 1/16 S6 BT RS401.
8" Spruce bears S14E 43.3 ft.; scribed SE 1/16 S6 BT.

Oregon State Board of Forestry metal location poster on 27" Hemlock BT.
Set 4" x 4" x 60" white painted Cedar post 1.0' S.E. of pipe.

West One Sixteenth corner common to Sections 6 & 7,
T. 2N, R. 9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E


Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY W 1/16 S6 S7 1958 RS401," 34 inches in ground, and from which a:

24" Hemlock bears N84E 7.7 ft.; scribed W 1/16 S6 BT RS 401.
48" Cedar bears N71W 61.8 ft.; scribed W 1/16 S7 BT.


Oregon State Board of Forestry metal location poster on 24" Hemlock BT.
Set 4" x 4" x 60" white painted Cedar post 1.0 ft. S.W. of pipe.

Dated February 19, 1958.

Established by



Richard A. Morris



Present and witnessed by Robert Sturm
Harold Russell