

CHAINS
FEET

3276.4	Stream, 2 feet wide, bears N 15° W.
4306.7	Stream, 2 feet wide, bears N 20° E.
4475.7	Spur ridge.
5179.4	The cor. of Secs. 21, 22, ²⁸ 26 & 27 bears S 04°35' W, a distance of 22.3 feet. The cor. determined by a stone, 24" x 14" x 16", marked X on the top face. from which the remains of the original bearing tree: A hemlock, 18 inches in diam., bears N 07° W, a dist. of 11.5 feet; scribes are burned out but axe marks and face visible. A metal location poster was found on ET. Adjustment of temp. stakes to true line position by single proportionate measurement and establishment of monuments. Relative to the compass bearing of the random line, the true line between Secs. 23 & 26 bears S 89° 59' W a dist. of 5232.5 ft.
True line Distance, feet	
0	The sec. cor. to Secs. 23, 24, 25 & 26 TLN R6W determined on retracement.
652	Set a 4" x 4" x 4" cedar post on true line of East side of road with a metal location poster marked Sec. 23/26, TLN, R6W, Sec. Cor. 652 ft. East.
2616.2	Point for the 1/4 cor. between Secs. 23 & 26. Adjustment from temp. stake 2640 - North 17.9 ft. East 10.3 ft. Set an iron pipe, 1 1/2 inches in diam., 3 ft. long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped 1/4 S23, S26 1949 199 from which: A fir snag, 26 inches in diam., bears N 66° E, a dist. of 9.6 ft. Scribed 1/4 S23, 199. A metal location poster above scribe on the fir snag bears N 66° E, a dist. of 9.6 feet, and marked S23/26, TLN, R6W, 1/4 cor., 9 ft., S 66° W. Placed 1/4 cor. stone found on retracement, at the edge of the iron pipe. Placed a mound of stone around iron pipe.

(Continued on page _____)