

CHAINS

SURVEY FOR THE OREGON STATE BOARD OF FORESTRY

February 1, 1951

Var. 22° E.

Restoration of the corner to Sections 17, 18, 19, & 20, Township 2 North, Range 6 West, W.M., Tillamook County, Oregon.

The point for corner determined by the remains of the original bearing trees:

A fir snag, 42 inches in diam., bears N 53° W, a distance of 35.0 feet (53 lks), did not chop into burl over old face. (The bearing called for in the original field notes is N 49° W).

A hemlock stub, 22 inches in diam., bears N 43° E, a distance of 27.7 feet (42 lks), did not expose further an old burnt out face. (The bearing called for in the original field notes is N 44° E).

A fir snag, 38 inches in diam., bears S 77° W, a distance 10.6 feet (16 lks), did not chop into burl. (The bearing called for in the original field notes is S 77° W).

A hemlock snag, 24 inches in diam., bears S 26° 30' E, a distance of 7.9 feet (12 lks), exposed scribe marks 6 R on edge of the burnt face.


(All distances measured from faces)

At the point for corner:

Set a 1½ inch iron pipe, 3 feet long, with an Oregon State Board of Forestry bronze cap stamped: T2N R7W S18 S17 S19 S20 1951 199.

Placed a metal location poster on the 38 inch fir snag B1, marked: Sec 19 T2N R6W Sec Cor 10.3 Ft. N 70° E.

Work done by Don Davis, Transitman; Richard Morris and Donald Newlen, Chainmen; Bill Kleeman and Adolf Berglund, Flagmen; under my direction.



Lyle E. Beyers  
Forest Engineer

