

CHAINS

SURVEY FOR THE OREGON STATE BOARD OF FORESTRY

of that portion of the range line between the 1/4 corner to Sections 25 & 30 and the 1/4 corner to Sections 24 & 19, Township 2 North, Ranges 5 & 6 West.

June 6, 1951

Var. 22° E.

Began at the 1/4 corner between Secs. 25 & 30, T. 2 N., R. 5 & 6 W, determined by a 1 1/2" iron pipe with an Oregon State Board of Forestry bronze cap stamped: 1/4 S 25 S 30 1950 199.

The 1/4 corner to Sec. 19 & 24 is visible from this point.

N 0° 45' W on true line between secs. 25 & 30.

1015.3

South edge of dirt road.

Set a 4" x 4" x 5' white cedar post with metal location poster marked: Sec line bet 25/30 T2N R5 & 6W 1/4 cor 1015.3 ft S0°45'E.

1519.7

North shoulder of Wilson River Highway.

Set a 4" x 4" x 5' white cedar post with metal location poster marked: Sec line bet 25/30 T2N R5 & 6W Sec Cor 1111.4 S0°45' E.

2117.0

Stream, 1/2 foot wide, flows N 60° E.

2564.0

Stream, 2 feet wide, flows N 45° W.

2631.1

Point for the cor to secs. 19, 24, 25 & 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron pipe, 1 1/2 inches in diam., 3 feet long, with an Oregon State Board of Forestry bronze cap stamped: T2N R6W R5W S24 S19 S25 S30 1951 199,

from which:

An alder, 5 inches in diam., bears S 20° 30' W, a distance of 50.9 feet scribed: S 25 199.

A fir stump, 40 inches in diam., bears S 62° 30' E., a distance of 79.7 feet scribed: T2N R5W S30 199 BT.

A fir stump, 34 inches in diam., bears S 88° W., a distance of 15.9 feet, scribed: R5W S25 199 BT.

Nailed a metal location poster on the 34" fir stump and marked it: Sec 25 T2N R6W Sec Cor 14.4 ft N 88° E.

Placed a mound of stone around monument.

3463.3

Stream, 2 feet wide, flows N 55° W.

3831.5

Stream, 6 feet wide, flows N 45° E.

4800.9

Stream, 32 feet wide, flows N 70° E.

4972.1

A 4" x 4" x 5' white cedar post on north edge of logging road marked with a metal location poster sec line bet 24/19 T2N R 5 & 6 W 1/4 cor 290.2 ft. North.