

CHAINS

RESTORED CORNER FOR THE OREGON STATE BOARD OF FORESTRY

November 15, 1951

The corner to sections 2, 3, 10, 11, Township 2 South, Range 7 West W. M., Tillamook County, Oregon.

ORIGINAL

Post (now missing) from which a:

- 30" Hemlock N71 $\frac{1}{2}$ W 27 lks; now missing.
- 7" Hemlock S20 $\frac{1}{2}$ W 25 lks; now missing.
- 6" V. maple S24E 19 lks; now missing.
- 26" Hemlock N77E 17 lks; now a 32" stub badly burnt; scribe marks visable in 1947, since burnt out.

RESTORED CORNER & BEARING TREES

At the point for corner

Set a 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T2S R7W S3 S2 S10 S11 1951 142" 2 $\frac{1}{2}$ ft. in ground. Raised mound of stone around it, from which a:


- 14" Fir stub bears S85W 16.8 ft.; scribed T2S R7W S10 BT 142.
 - 78" Fir stub bears S06E 29.2 ft.; scribed T2S R7W S11 BT 142.
 - 38" Fir snag bears N02W 30.0 ft.; scribed T2S R7W S3 BT 142.
 - 62" Fir snag bears N71E 52.0 ft.; scribed T2S R7W S2 BT 142.
- (Distances measured from center of bearing trees).

Nailed a metal location poster on the 78" fir snag BT & marked it: Sec 3 T2S R7W Sec Cor 27.4 ft. S04E.



Restored by

Walter M. Robertson



Walter M. Robertson

Present & Witnessed by

Don Davis
Don Davis Asst. Forest Engineer OSBF

Present & Witnessed by

Richard Morris
Richard Morris Chairman OSBF