

Cour Surveyor's Record, Tillamook Cour Oregon

T 6 S. R 10 W.

Rewitnessed corners

Mervin Whitmore U. S. Forest Service

CHAINS		
Sec. Cor	The original post with iron pipe alongside for cor. A 20" fir, S.64°W. 28 ft. mkd. T6SR10WS34BT. (New BT) A 16" fir, N.29°W. 16½ ft. mkd. T6SR10WS27BT. (New BT) A 13" fir, N.35°E. 12½ ft. mkd. T6SR10WS26BT. (New BT) A 19" fir, S.69°E. 21½ ft. mkd. T6SR10WS35BT. (New BT)	
27 26 34 35	In the presence of Max Carver. Sept. 11, 1959	
	<i>Lincoln County</i>	
Sec. Cor	Set a fir limb post for cor. A 40" dead fir snag, S.1°W. 70 lks. mkd. S33BT BT. (Old BT) A 40" dead fir snag, N.27°E. 48 lks. mkd. T6SR10. (Old BT) A 51" spruce, N.39°W. 31½ ft. mkd. T6SR10WS28BT. (New BT) A 14" spruce, N. 40°E. 37½ ft. mkd. T6SR10WS27BT. (New BT) A 36" cedar, S.16°E. 17 ft. mkd. T6SR10WS34BT. (New BT) A 19" alder, S.35°W. 46 ft. mkd. T6SR10WS33BT. (New BT)	
28 27 33 34	In the presence of Leonard Whitmore and Max Carver. July 2, 1959	
	<i>Lincoln County</i>	
¼ Cor.	Set iron bar in mound of stone for cor. (No bearing trees.) This corner is set by proportionate measurement and sets about 160 ft. E. of Power line and about 40 ft. S. of spur road leading to power line.	
27 34	In the presence of Max Carver. Sept. 15, 1959	
	<i>Lincoln Co.</i>	
Sec. Cor	The original post. A 55" spruce N.50°W. 23 ft. mkd. T6SR10WS20BT. (New BT) No other tree within limits to mark.	
20 21	In the presence of Bob Madison and Lem Apple. March 18, 1959.	
	<i>Lincoln Co.</i>	
Sec. Cor.	Set post for cor. A 32" fir, N.79°E. 28 ft. mkd. T6SR10WS16BT. (New BT) A 37" fir, N.60°W. 61 ft. mkd. T6SR10WS17BT. (New BT)	
17 16	In the presence of Lem Apple. March 18, 1959	
	<i>Tillamook Co.</i>	
¼ Cor.	Set a fir limb post for cor. mkd. ¼S28 on E. and ¼S29 on W. side. A 15" fir, S.56°E. 14 ft. mkd. ¼S28FSBT. (New BT) A 16" fir, N.77°W. 11 ft. mkd. ¼S29FSBT. (New BT)	
29 28	In the presence of Max Carver Sept. 23, 1959	
	<i>Lincoln Co.</i>	
	(6. 5.10)	
BOOK 2		X
404		404