

Dependent Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 7 W

 $\frac{1}{4}$ S 17

S 20

1965

from which

A fir, 9 ins. diam., bears N. 22° W., $101\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S17 BT.

A fir, 8 ins. diam., bears S. $1\frac{1}{2}^\circ$ E., $82\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S20 BT.

The corner is located at the NW. cor. of partially logged area, edge bears E. and S.

Ascend 65 ft. over NE. slope.

46.60 Spur ridge, bears NW. and SE.; desc. 310 ft. over SW. slope, changing to W. slope.

69.40 Ravine, drains N. 20° W.; asc. 100 ft. over NE. slope.

76.40 Top of ascent, slopes N.; desc. 40 ft. over NW. slope.

78.55 The cor. of secs. 17, 18, 19, and 20.

Land, mountainous.

Soil, rocky clay.

Timber, fir, alder, cascara, wild cherry, elderberry and maple; undergrowth, vine maple, salal, fern, willow, salmonberry, hazel, devil's club and Oregon grape.

N. $89^\circ 53'$ W., bet. secs. 18 and 19.

Descend 40 ft. over NW. slope, through heavy timber and dense undergrowth.

1.70 Ravine, drains N. 20° W.; asc. 35 ft. over NE. slope.

4.30 Spur, slopes N.; desc. 155 ft. over NW. slope.

10.70 Creek, 4 lks. wide, course NE.; asc. 300 ft. over steep SE. slope.

27.00 Spur, slopes N. 60° E.; asc. 100 ft. over broken NE. slope.

39.32 The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with the original basalt stone, 24 x 14 x 12 ins., firmly set 18 ins. in the ground, mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 7 W

 $\frac{1}{4}$ S 18

S 19

1965

from which

A fir, 18 ins. diam., bears N. 73° W., 49 lks. dist., mkd. $\frac{1}{4}$ S18 BT.