

70 $\frac{1}{4}$ Cor on N. Bdy sec 2. 2N 10W
 Cor in place f.w. marked
 Hemlock 30" hrs 54°45'W 44'
 " 22" " S17°30'E 87.3

Present J. McKimmens R.B. Hayes

71 Cor to Sec 24, 25, 19 & 30, T. 1 N. R. 10 W.
 Set post from which:
 Fir - N. 44° W. 27 lbs.
 " - S. 35° W. 30 lbs.

72 Corner to Secs. 16, 17, 20 & 21 T. 3 S. R. 10 W.
 Post f.w.
 Spr. 12" S. 41° 20' E. 63.9
 " 8" N 85° 7' E. 81.4
 U.S. Jackson June 1912.
 Present H. Farmer.
 U.S. Edwards.

73 Quarters Corner to Sec. 19, 24, 25 & 30,
 T. 1 N. R. 8 W. W. M.
 I drove gal. iron pipe 2" dia, 2" south
 of iron marks on B.T. N. 44° W 27 lbs, from
 corner. Distance to pipe 18'.
 Drove iron pipe 10" North. E. of Marks on
 N.W. S. 35° W 30 lbs from corner. Dist. to pipe 6'.
 Drove iron pipe in 5" hem., 24' S.E. of
 corner.
 Drove iron pipe 1' 10" East of tree on the
 West of the corner. Distance to pipe 8' 10" from
 corner.
 Nov 26, 1912.

Present Geo. T. Kielern
 John H. Kerach.
 Wm Ryan

74 Cor to Secs 16, 17, 20 & 21 3 S. R. 10 W. W. M.
 N.W. Corner Schoolhouse N49.28E 91.5 ft.
 S.W. Corner schoolhouse N74.37E 72.2 ft.
 November 30 1914

Present
 U.S. Edwards
 E. E. Allen
 P.W. Barrett

75 $\frac{1}{4}$ Sec. Cor between Secs. 17 & 20 3 S. R. 10 W.
 B.T. 6" Spruce 540.41E 43.85 ft
 Spruce limb N 0° 41' E 30.0 ft
 " " 50° 41' W 30.0 ft

Present, U.S. Edwards
 G. J. Poytky
 A. Gustrom June 29 1913

76 M.C. Between Sec. 21 & 22 T. 1 N. R. 10 W.
 Spruce limb N 3° 22' W 31.26
 " " 576° 46' W 91.51'
 " " 531° 55' E 35.38'
 " " 551° 45' E 46.53'
 " " 580° 18' E 44.18'

Cross on SW Wing of Concrete
 Abutment to Bridge
 N 39° 04' E 190.06' 1915

77 M.C. Between Sec. 23 & 26
 T. 3 N. R. 10 W. of W.M. Br. Bank.
 Nebalem P. Old B.T. 90° sp N 75° W 26.4' LEFT
 19" Alder, 566° 44' W, 105A'
 10" Twin Alder 558° 10' W, 159.9'

Across River - 24" Cottonwood 561° 39' E
 These trees were established
 to replace Old B.T. 90° sp Cut by Tohl.
 Present: W. Anderson, W. Tohl, C. Himple,
 Geo. McKimmens. 1915.

SEE
 CL19
 PAGE 71