


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

1/4 corner set in 1878 by Henry Meldrum

BTs - A 36" fir brs. N58W 43 lks

A 4" maple brs. S27E 70 lks



Description of corner evidence found:

Found old vinepost mkd 1/4 S by M. Whitmore, 1954 from which

A 48" snag brs. N58W 28.0 ft (ORIG)
with 1/4 in bark (faint) - in 1954 M. Whitmore scribed 1/4 BT in addition to original marks (see Book 1 P. 240) JK

An 13" alder brs. S85E 7.5 ft
scribing visible
scribed by M. Whitmore in 1954

Description of monument and accessories established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap mkd
T4S R10W

1/4 26
35
1970
650

Put a fence post with signs ± 5 ft south facing west
± 5 ft east facing north

Office of CLATSOP COUNTY SURVEYOR County of TILLAMOOK
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 8th day of July, 1970, at o'clock m., (signed)
[Signature] (COUNTY OFFICIAL) [Signature] (DEPUTY)

REGISTERED
OREGON
LAND SURVEYOR
[Signature]
JULY 10, 1964
TOM O. McCULLOUGH
650

BOOK 5

4/17/70