

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner had never been established.

DIAGRAM Q
Section 6
C-N-SE-NW
1/256

Reference:

Plat dated July 1973 by
Timberland Services, Inc
under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked:

T 6 S R 10 W
S 6
C-N-SE-NW
1/256
1973
RLS 942

by proportional measurement.

From which a:

- 30" Spruce S 36° E 22.6 ft.
mkd "CNSENW 1/256 S 6 BT"
- 44" Spruce South 7.4 ft.
mkd "CNSENW 1/256 S 6 BT"

Witnessed: M. Jackson

Office of County Surveyor County of Tillamook,
State of OREGON I hereby certify that the within instrument was filed in this office
for record on the 20th day of August, 1973, at 8⁵² o'clock A. m., (signed)

[Signature] by *[Signature]*
(COUNTY OFFICIAL) (DEPUTY)

Set this 26th day of July 1973.

245

BOOK 5 *[Signature]*

Graduate Forest Engineer
Form R6-7100-57 (9/66)

TIMBERLAND SERVICES, INC.
P.O. Box 668 - Albany, Ore. 97321
Phone: 928-3539

REGISTERED
PROFESSIONAL
LAND SURVEYOR
[Signature]
OREGON
JULY 17, 1970
KENNETH M. WIGHTMAN II
942