

Remonumentation of Certain Original Corner Points,  
T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

T 4 S R 9 W  
S 19 | S 20  
S 30 | S 29  
1978

from which new bearing trees

An alder, 28 ins. diam., bears N. 62° E., 46 lks.  
dist., mkd. T4S R9W S20 BT on bark.

An alder, 24 ins. diam., bears S. 52½° W., 86 lks.  
dist., mkd. T4S R9W S30 BT on bark.

An alder, 16 ins. diam., bears N. 85° W., 14 lks.  
dist., mkd. T4S R9W S19 BT on bark.

Set a 5 ft. steel fence post alongside iron post.

(Remonumenting corners established by Charles E. Branson,  
U . S. Deputy Surveyor, in 1898)

The cor. of secs. 7, 8, 17, and 18, perpetuated and re-  
corded by Mervin Whitmore, Deputy County Surveyor, in  
1957, monumented with an unmarked cedar post, 2 x 6 ins.,  
firmly set, projecting 30 ins. above ground, from which  
the remains of the original bearing trees:

A fir, 40 ins. diam., bears N. 12° 10' E., 76½ lks.  
dist., no marks visible on opened blaze.

A decayed fir stump, size indeterminate, bears  
S. 77½° W., 28½ lks. dist., no marks visible.

A fir, 35 ins. diam., bears N. 75° W., 89 lks.  
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 4 S R 9 W  
S 7 | S 8  
S 18 | S 17  
1978

from which new bearing trees

A fir, 8 ins. diam., bears S. 75° E., 3½ lks.  
dist., mkd. T4S R9W S17 BT.

An alder, 18 ins. diam., bears S. 15° W., 29 lks.  
dist., mkd. T4S R9W S18 BT on bark.

Reset cedar post and set a 5 ft. steel fence post  
alongside iron post.

The ¼ sec. cor. of secs. 8 and 17, monumented with a  
basalt stone (not of record), 18 x 12 x 6 ins., firmly  
set, in a mound of stone, 3 ft. base, 1 ft. high, pro-  
jecting 8 ins. above ground, mkd. ¼ S8 on N. and ¼ S17  
on S. faces, from which the remains of the original  
bearing trees: