

REWITNESSED CORNER FOR STATE OF OREGON - DEPARTMENT OF FORESTRY
4907 Third St., Tillamook, Oregon 97141

Section corner common to Sections 29, 30, 31 and 32, T2N, R7W,
W.M., Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, September 16, 1891.

17" x 8" x 6" Basalt stone with 5 notches on East and 1 notch on
South; in place.

28" Hemlock bears N32E 33 lks.; now a 13" x 3 ft. high badly rotted
stub with no scribes visible.
20" Hemlock bears S66E 130 lks.; missing.
12" Hemlock bears S59 1/2W 59 lks.; missing.
20" Hemlock bears N85W 10 lks.; missing.

RESTORATION by Louis W. Amort RE2311 June 7, 1952 (Book 2, page 212,
Tillamook County Records).

1 1/2" x 36" galvanized iron pipe with 3" bronze cap 30" in ground,
with corner stone on west side of pipe, in mound of stone; in
place.

48" Fir stub 15 ft. high bears N39 1/2E 15.3 ft.; now rotted with
scribes T2N R7W S29 BT visible. Also letters D and W chopped
on stub.
36" Fir stump bears S03W 100.7 ft.; scribes T2N R7W S31 BT RE2311
visible.
52" Fir snag bears S79E 101.2 ft.; now a rotted stump with scribes
T2N R7W S32 BT visible.
72" Fir stump bears N65W 65.0 ft.; now rotted with scribes T2N R7W
S30 BT visible.

REWITNESSED September 27, 1990

Var. 21 1/2E

From above pipe with marks "LS1998 1990" added, a:

11" Fir bears N59E 17.8 ft. to face; scribed T2NR7WS29BT.
15" Fir bears S23E 22.3 ft. to face; scribed T2NR7WS32BT.
13" Fir bears S70W 3.1 ft. to face; scribed T2NR7WS31BT.
11" Fir bears N17 1/2W 9.7 ft. to face; scribed T2NR7WS30BT.

Metal location poster on new BTs.

Also 1952 metal location poster on 48" Fir stub BT.

3/4" brass washer marked "LS1998" nailed to face of new Fir BTs.

Present and witnessed by Clifford R. Foster and Richard A. Henningsen.

Rewitnessed by David B. Buchholz under my direction.
David B. Buchholz, LS2272

