TILLAMOOK COUNTY SURVEYORS OFFICE COURTHOUSE, TILLAMOOK, OREGON 97141

E 1/16 CORNER SECTIONS 5 & 8 T.5S., R.10W., W.M. (Government Lot Corner 35 & 34 Section 5) (Government Lot Corner 3 & 2 Section 8)

not . stamped I found a 6"X 8"X 20" stone marked with an X, (see T.C.S. map #B-1460). I set a 1 1/2"X 36" iron pipe with a 3" Tillamook County Surveyors Brass Cap top approximately 6" below the surface in an irregular mass of concrete S.86'35'W. 26.91' of the found stone for a Witness Corner.

History of found monument

This corner originally was a post with charred stake, in mound of earth with pits set by J.W. Meldrum under contract #166 dated January 10, 1872. Andrew M. Austin in T.C.S. Book "S3" at Page 402 dated May 21 & 22, 1902 reestablished the corner midway between the section corner and the 1/4 corner by setting a 6"X 8"X 20" stone marked "X". This stone was found by Douglas H. Kellow PLS 2027 on T.C.S. map B-1460 dated October 16, 1990 very close to the proportion position and was accepted as the 1/16 corner.

I set this witness corner in to preserve the location of this corner before the construction of a ditch line planned to go north and south along the 1/16 line.

Basis of Bearings for the above bearing is from the found stone marked "X" at the said 1/16 to the T.C.S. Brass Cap at the CE 1/16 corner (SE Corner Government lot 14) = $5.0^{\circ}08'44$ "E. the value shown on T.C.S. Map #B-1460.

Supreye and Constances of pecond

Surveys and Rewitnesses of record

New Accessories

*72" light hat section post N.3 10 "E. 139.15'.

Location of Monument

This corner is located approximately 27' West of an N-S fence line, soon to be a ditch, and 140 South of the toe of a dike on the south side the Little Nestucca River.

In the name of Al Dunnel and Dan Noblet

In the presence of Al Dvorak and Dan McNutt

July 24, 1991

Title:

PROFESSIONAL LAND SURVEYOR

OREGON
JULY 14, 1967
ALLAN E. DUNCAN
7 9 3

REGISTERED