

**SOUTHEAST TOWNSHIP CORNER TO TOWNSHIP 4 NORTH, RANGE 9 WEST, WILLAMETTE MERIDIAN.**

**HISTORY:**

- Record No. 1 September 19, 1891 - Manius Buchanon, GLO Deputy Surveyor in survey of the South boundary of T4N R9W; Set post for corner to T3&4N, R8&9W from which:  
A 14" Hemlock bears N51'E, 56 lks. (36.96');  
A 10" Hemlock bears S46'30'E, 33 lks. (21.78');  
A 10" Spruce bears S89'30'W, 113 lks. (74.58');  
A 10" Alder bears N47'15'W, 68 lks. (44.88').
- Record No. 2 1893 - Henry Meldrum, GLO Deputy Surveyor in survey of the West boundary of T4N, R8W; I begin at the corner to T3&4N, R8W (Closing Township corner on the West boundary of R8W) run North on East boundary of T3N R9W for West boundary of T4N R8W.  
52.98 chs Intersect South boundary to T4N R9W at a point 46 lks. West of the closing corner to T3N R9W, which corner is a post, 4 ins. sq., firmly set in the ground from which:  
A 12" Hemlock bears S27'E, 34 lks. (22.44');  
A 50" Hemlock bears S13'W, 41 lks. (27.06').  
Thence I run East 1.16 chs. (76.56') to the Southeast corner of T4N R9W, (crossing East Creek, 10 lks. wide, runs N.) the cor. to T4NR9W is a post, 5 ins. sq., firmly set in the ground, marked T4NS31 on NE, R8WS31 on SE, and R9WS36 on NW faces, from which:  
A 14" Hemlock bears N51'E, 56 lks. (36.96');  
A 10" Hemlock bears S46'30'E, 33 lks. (21.78');  
A 10" Spruce bears S89'30'W, 113 lks. (74.58');  
A 10" Alder bears N47'15'W, 68 lks. (44.88').  
Note: The marks on post and on two witness trees were changed by me in order to make said marks correspond with the facts, as Section 31 surrounds this corner on three sides.
- Record No. 3 December 31, 1965 - Harold J. Russell, Oregon Land Surveyor No. 707; "ORIGINAL Post (now missing) from which: [calls to GLO witnesses as follows:]  
NE BT = "now 24" 3' high stub, face and scribes rotted away."  
SE BT = "now missing, roots in place."  
SW BT = "now missing."  
NW BT = "now missing, pile of debris in place."  
East Creek, course N, bears West 75 lks.; in place.  
RESTORED Set 1-1/2" X 36" galvanized iron pipe with 3" bronze cap marked 'OREGON STATE BOARD OF FORESTRY T4N R9W S36 T4N R8W S31 1965 RS 707', 34 inches in ground, on east edge cat road, in mound of rock, and from which a:  
28" Spruce bears N86-1/4W 89.2 ft.; scribed T4N R9W, S36 BT RS 707.  
30" Hemlock bears N36-3/4W 90.4 ft.; scribed T4N R9W S36 BT.  
Set 4" X 4" X 60" white painted Cedar post 1.0 ft. NW of corner pipe. Oregon State Forestry Department metal location poster on 30" Hemlock BT." (Bearing Tree Book page 273-20, Clatsop County Survey Records.)

