

CLOSING TOWNSHIP CORNER ON THE EAST RANGE LINE, COMMON TO TOWNSHIP 3 NORTH, RANGE 6 WEST AND TO TOWNSHIP 4 NORTH, RANGE 6 WEST, WILLAMETTE MERIDIAN.

HISTORY:

Record No. 1 November 16, 1891 - Henry Meldrum, GLO Deputy Surveyor in survey of the East boundary of T3N, R7W; North between 1-6 ...80.00 Set post 4-1/2 ft long 4 ins Sq 24 ins in ground for corner to Townships 3 and 4 North Ranges 6 and 7 West [Note; this corner later becomes the Corner to T3&4N R7W].

*GLO 3N
Pages
15-14*

Record No. 2 September, 1892 - John McQuinn, GLO Deputy Surveyor in survey of the East boundary of T4N, R6W; "at 5 mile 77.93 chains Intersect the East boundary of Tp.4N. R.7W. at a point 15.45 chains South of the 1/4 Sec. cor. on the East side of (which is a post as described in the field notes furnished me by the surveyor general) sec. 36, at point of intersection is a hemlock 6 inch in diam. for closing cor to Tps. 3 and 4 N. R.6W. marked ... from which:
An 18" Hemlock bears N45°E, 31 lks. (20.46');
A 12" Hemlock bears S19-1/2°E, 60 lks. (39.60')
A 16" Hemlock bears N62-1/2°W, 64 lks. (42.24')

*GLO 3N
Pages 115*


Record No. 3 June 19, 1893 - Lincoln E. Wilkes, GLO Deputy Surveyor in survey of East line of T3N R6W; North retracing the range line on the West boundary of Section 6.
50.60 to a point from which the corner as established for corner to Townships 3&4 North, Ranges 6&7 West [See Record No. 1] ... After destroying all marks on bearing trees and stake which refer to sections 31 and 6.
73.85 the closing corner to Townships 3 and 4 North Range 6 West which is marked by a hemlock 6 ins diam. ... from which:
A 14" Hemlock bears N47°30'E, 32 lks. (21.12');
A 5" Hemlock bears S17°E, 59 lks. (38.94');
An 8" Hemlock bears N62°30'W, 69 lks. (45.54').

*GLO Book
3N Pages
97*

Record No. 4 February 21, 1955 - Louis W. Amort, Oregon Engineer No.2311; "ORIGINAL 6" Hemlock, now missing. From which a: [Calls to GLO bearing trees as follows]
NE BT = "now 22" snag, trace of scribe visible on edge of burnt out face."
SE BT = "now missing, point falls in old skid road."
NW BT = "now 13" uproot, roots and root hole in place, scribes BT visible, upper face burnt out."
"RESTORED Set 1-1/2" X 36" galvanized iron pipe with 3" bronze cap marked 'OREGON STATE BOARD OF FORESTRY T4N R6W S6 CC T3N 1955 RE 2311,' 32 INCHES IN GROUND, IN MOUND OF STONE, AND FROM WHICH A:
5" Fir bears S67°E 66.0 ft.; scribed T3NR6WS6CCBT.
41" Cedar stump bears N20°E 13.5 ft.; scribed T4N R6WS31CCBTRE2311.
Oregon State Board of Forestry metal location poster on 41" Cedar stump BT. Set 4" X 4" X 60" white Cedar post 1.5' NW of pipe." (Bearing Tree Book page 199-3, Clatsop County survey Records.)


7N 6W 14

*BOOK I
Page 202*



1 of 2

Record No. 5 August, 1987 - George Ford, Oregon Land Surveyor No. 2210; "FOUND 1-1/2" PIPE,
41" CEDAR STUMP N20°E AT 13.5 FT. SCRIBED,
O.S.B.F. TAG DATED 2/16/55.
SET REBAR WITH CAP NEXT TO PIPE. MONUMENT IS
S89°57'22"W AT 1.28 FT. OF STANDARD RANGE LINE. R.P.
ED:
14" FIR N62°E AT 34.6 FT.
20" FIR S10°W AT 10.0 FT.
24" FIR S84°W AT 23.5 FT.
(County Survey No. B-8627, Clatsop County Survey
Records.)



20F2