

REWITNESSED CORNER FOR OREGON DEPARTMENT OF FORESTRY
4907 Third St., Tillamook, Oregon 97141

Section corner common to Sections 20, 21, 28 and 29, T3S, R9W, W.M., Tillamook County, Oregon.

ORIGINAL by Samuel G. Caudle, September 23, 1880.

Post; missing.

24" Fir bears N85°E 23 lks.; missing, root crown bears N75°E.

30" Fir bears S85°E 16 lks.; missing, stump hole in place.

24" Fir bears N18°W 65 lks.; missing, falls in edge of road.

RESTORATION by U.G. Jackson, County Surveyor, February, 1913 (Not Recorded).

Richard A. Morris, (Book 2, Page 333, Tillamook County Records) reports finding a 4"x4"x30" scribed Fir post, (missing) with a 1"x52" galvanized iron pipe, 28" in ground wired to the East side of the post; found pipe with wire wrapped around it laying on ground out of place.

REWITNESSED by William E. Anderson, RE1697, March 21, 1956, (Book 2, Page 333, Tillamook County Records).

From above pipe a:

19" Fir bears N46°E 75.0 ft.; now a 27"x5½ ft. high stump with the bark peeled off and top covered with galvanized steel sheeting, no evidence of face visible.

29" Fir bears S87°E 103.3 ft.; now a 35"x4 ft. high badly rotted stump with face closed.

22" Fir bears S42°W 25.4 ft.; now a 26"x5 ft. high badly rotted stump with portions of scribes visible in bark at edge of closed face.

42" Fir bears N50°W 93.1 ft.; now a 54"x5 ft. high rotted stump with portions of scribes visible in bark at edge of closed face.

4"x4"x72" white painted Cedar post bears SE 1.5; now S39°E 2.1 ft.

RESTORATION by Lynn M. Roseberry, U.S. Cadastral Surveyor, Group #350, 1962.

2½"x28" iron post with 3" brass cap 24" in ground; in place.

NOTE: Roseberry reports, "Reset local corner material alongside the iron post".

RESTORATION by John L. Carlich, County Surveyor, LS287, March 22, 1978 (Rewitness Bin #526 Tillamook County Records).

Placed a 10" tile and cement around Roseberry's post; in place.

REWITNESSED October 10, 1996

Var. 19½°E

From Roseberry's post with marks "LS1998 1996" added a:

8" Fir bears N78°E 25.0 ft. to face; scribed T3SR9WS21BT

7" Fir bears S18°E 21.2 ft. to face; scribed T3SR9WS28BT.

7" Fir bears S55°W 12.3 ft. to face; scribed T3SR9WS29BT.

8" Fir bears N11°W 3.1 ft. to face; scribed T3SR9WS20BT.

Metal location poster on new BTs and Anderson's 29" Fir.

3/4" brass washer marked "LS1998" nailed to face of new BTs.

Present and witnessed by David B. Buchholz and Clifford R. Foster.

Rewitnessed by



SURVEYED BY:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Anthony J. Klosterman

OREGON
July 21, 1982
Anthony J. Klosterman
1998

6505 GRANDVIEW HGTS.
TILLAMOOK, OR 97141
EXPIRES JUNE 30, 1997