


TILLAMOOK COUNTY SURVEYORS OFFICE TILLAMOOK COUNTY COURT HOUSE  
201 LAUREL AVENUE TILLAMOOK, OREGON 97141

1/4 CORNER COMMON SECTIONS 26 & 27, T.1N.,R.10W.,W.M.



I FOUND A 1 1/2" IRON PIPE WITH A 3" O.S.B.F. BRASS CAP, (SEE T.C.S. REWITNESS BOOK 2 PAGE 438).  
I ENCASED THE FOUND IRON PIPE WITH BRASS CAP IN AN IRREGULAR MASS CONCRETE.

**HISTORY OF FOUND MONUMENT**

I FOUND THIS MONUMENT TO BE AS DESCRIBED IN T.C.S. REWITNESS BOOK 2 AT PAGE 438 AND THE REFERENCES FOUND AND/OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

(BOOK 2 PAGE 438) 18" HEMLOCK S.75 1/2'E. 27.3', REPORTED IN REWITNESS BOOK 5 AT PAGE 341 AS A 26" STUMP, FACE GROWN OVER; (FOUND, NOW A ROTTED STUMP, 3' HIGH, FACE OVERGROWN).

(BOOK 2 PAGE 438) 19" HEMLOCK N.79 3/4'W. 13.5', REPORTED IN REWITNESS BOOK 5 AT PAGE 341 AS A 26" 26" BURNT, UPROOTED STUMP, FACE GROWN OVER; (FOUND, NOW A ROOT HOLE).

(BOOK 5 PAGE 341) 44" HEMLOCK S.51'W. 57.4'; (FOUND, NOW A 48" ROTTED HEMLOCK STUMP, 3' HIGH, SCRIBES VISIBLE ON PARTIALLY HEALED FACE).

(BOOK 5 PAGE 341) 64" SPRUCE STUMP N.33 3/4'E. 47.0'; (FOUND, NOW A 64" ROTTED SPRUCE STUMP, 7' HIGH, MARKS ROTTED OFF, O.S.B.F. YELLOW METAL LOCATION POSTER ATTACHED).

(BOOK 5 PAGE 341) 4"X 4"X 60" WHITE PAINTED CEDAR POST 1.0' NE; (FOUND, NOW ROTTED OFF AND LAYING ON GROUND).

**NEW ACCESSORIES**

- \*10" HEMLOCK S.69'W. 16.73' SCRIBED 1/4S27CSBT
- \*13" HEMLOCK NORTH 23.69' SCRIBED 1/4S26CSBT
- \*72" LIGHT HAT SECTION POST NORTH 1.50'

DISTANCES WERE MEASURED TO A NAIL WITH T.C.S. BRASS WASHER DRIVEN IN THE FACE BETWEEN THE SCRIBED "B" AND "T".

ATTACHED A YELLOW METAL LOCATION POSTER ON A 10" HEMLOCK ± N.27'W 52'.

\*INDICATES YELLOW METAL TILLAMOOK COUNTY SURVEYORS LOCATION POSTER ATTACHED.

**SURVEYS AND REWITNESSES OF RECORD**

B-419	DEC. 1959	R. A. MORRIS	LS 401
A-1102	NOV. 1963	R. A. MORRIS	LS 401
B-540	DEC. 1967	H. RUSSELL	LS 707
REWITNESS BOOK 2 PAGE 438	DEC. 1959	R. A. MORRIS	LS 401
REWITNESS BOOK 5 PAGE 341	4-4-1975	H. RUSSELL	LS 707

**LOCATION OF MONUMENT**


THIS CORNER IS LOCATED APPROXIMATELY 75' SOUTH OF A GRAVEL LOGGING ROAD ON A FLAT AREA.

THIS CORNER IS A PROPORTION CORNER SET BY MAP B-419. NO MEASUREMENTS WERE TAKEN TO DETERMINE ITS VALIDITY.

IN THE PRESENCE OF AL DVORAK AND DAN McNUTT

APRIL 22, 1999

Title



*Allan E. Duncan, C.S.*

