TILLAMOOK COUNTY SURVEYORS OFFICE COURTHOUSE, TILLAMOOK, OREGON 97141

1/4 CORNER COMMON SECTION 25 &36 T.3N;R.10W;W.M.

R10W	
S 25	I FOUND A 2" IRON PIPE WITH A 3" TILLAMOOK COUNTY SURVEYORS
1/4	BRASS CAP FLUSH WITH THE GROUND, ORIGIN UNKNOWN.
s 36	I ENCASED THE FOUND IRON PIPE IN AN IRREGULAR MASS OF
RS 287	CONCRETE.
1969	

HISTORY OF FOUND MONUMENT

GENERAL LAND OFFICE AUGUST 20, 1873

SET POST FOR 4 SECTION CORNER. (NOW GONE).

4" V. MAPLE S.42°W. 10 LINKS. (NOW GONE).

5" BARBERRY N.18°E. 42 LINKS. (NOW GONE).

BOOK S3 PAGE 312 AND AMA 9 PAGE 174 A.M. AUSTIN JUNE 9, 1900

SET SPRUCE STAKE FROM OLD GOVERNMENT WITNESS AND OLD STAKE BADLY DECAYED; (NOW GONE)

30" HEMLOCK S.28°W. 42 LINKS. (FOUND, NOW A 40" ROTTEN STUMP 7' TALL).

30" HEMLOCK N.13°E. 57 LINKS. (FOUND ROTTED REMAINS AT POSITION. THE BEARING WAS TRANSPOSED WHEN IT WAS COPIED FROM FIELD NOTEBOOK AMA 9 PAGE 174 INTO THE S3 BOOK TO N.31°E.).

BOOK 4 PAGE 50 W. E. ANDERSON, 1949

45" HEMLOCK S.23°W. 26.2'. (FOUND, PROBABLY SAME TREE AS AUSTIN SW B.T.).

36" HEMLOCK N.14°W 37.6'. (NOW GONE).

28" HEMLOCK N.79°W. 14.5'. (NOW 30" HEMLOCK STUMP 5' TALL).

SURVEYS AND REWITNESSES OF RECORD B-675 FALL 1974 JOHN L. CARLICH LS 287 A-3822 JUNE 1979 JOHN L. CARLICH LS 287 A-1797 SEPTEMBER 1969 JOHN L. CARLICH LS 287 A-1071 May 1963 W. A. MARKHAM PΕ 1842 A-2283 JULY 1972 W. A. MARKHAM 1842 \mathbf{PE} A-5036 10-08-1964 W. A. MARKHAM PE 1842 A-3481 AUGUST 1963 W. A. MARKHAM PE 1842 F-40-277 JUNE 1955 W. A. MARKHAM 1842 $\mathbf{p}\mathbf{E}$ F-2-6 DATE UNKNOWN W. E. ANDERSON BOOK 4 PAGE 50 1949 W. E. ANDERSON B-1936 11-07-1995 ALLAN E. DUNCAN 793 LS P-303 12-05-1995 ALLAN E. DUNCAN LS 793 P-193 11-02-1993 LESLIE G. KEENON LS 1080 B-1799 04-15-1994 ERIC N. HALLER LS 2148

PAGE 1 OF 🏃

A-6915	12-17-1994	ERIC N. HALLER LS 2148
P-420	11-23-1997	ERIC N. HALLER LS 2148
B-2187	03-31-1998	ERIC N. HALLER LS 2148
P-493	12-12-1998	ERIC N. HALLER LS 2148
P-612	12-17-2000	ERIC N. HALLER LS 2148
BOOK S3 PAGE 128	07-13-1897	A. M. AUSTIN
BOOK AMA 14 PAGE 56	07-13-1897	A. M. AUSTIN
BOOK S3 PAGE 312	06-09-1900	A. M. AUSTIN
BOOK AMA 9 PAGE 174	06-09-1900	A. M. AUSTIN

NEW ACCESSORIES

*15" HEMLOCK S46°55'23"E 2.99' SCRIBED T3NR10W 1/4S36BT. MEASUREMENTS WERE TAKEN TO A NAIL WITH T. C. S. BRASS WASHER BETWEEN SCRIBED B & T.

*14" HEMLOCK S.53°21'11"W. 19.46' SCRIBED 1/4S36BTCS. MEASUREMENTS WERE TO A NAIL WITH T. C. S. BRASS WASHER BETWEEN SCRIBED B & T.

*6" HEMLOCK N.34°09'01"W. 7.24' SCRIBED 1/4825BTCS. MEASUREMENTS WERE TO A NAIL WITH T. C. S. BRASS WASHER BETWEEN SCRIBED B & T.

*LIGHT HAT SECTION POST N.20°E. 1.5'.

"*" INDICATES YELLOW METAL TILLAMOOK COUNTY LOCATION POSTER ATTACHED.

BASIS OF BEARINGS IS FROM PARTITION PLAT 2001-03

LOCATION OF MONUMENT

THIS CORNER IS LOCATED APPROXIMATELY 700' EAST OF STATE HIGHWAY #53, APPROXIMATELY 1500' NORTH OF MIAMI FOLEY COUNTY ROAD, AND APPROXIMATELY 100' WEST OF THE PPGL POWER LINES.

REGISTERED

IN THE PRESENCE OF AL DVORAK, DAN MCNUTT, AND JOE JENSEN

MAY 5, 2002

TITLE:

PROFESSIONAL LAND SURVEYOR

OREGON
JULY 14, 1987
ALLAN E. DUNCAN
793

NENEWAL /2-3/-03

PAGE 2 OF 2

DATE MAY 3 0 2002

BOOK 7 348