

USDA-FOREST SERVICE

Index

CORNER RECORD (SEARCH)

File No. Z-21 PROJ. NO. Horn CORNER SEC  
 TOWNS. 3S. & 4S. RANGE 10 W. R.D. Hebo COUNTY Tillamook GCDB# 600100  
 MERID. W.M. FOREST SIU STATE Oregon

<p><b>CORNER DIAGRAM</b></p>	<p><b>DESCRIBE CORNER MONUMENT FOUND</b></p> <p>Found 2-1/2" Brass Cap on 2-1/2" I. Pipe, Flush with ground</p>																																			
<p><b>PHOTO IDENTIFICATION DATA</b></p> <p>Photo No. _____          Filed At. _____          Obj. Ident. _____          Ident. By _____          Signature _____</p>	<p><b>DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND</b></p> <table border="1"> <thead> <tr> <th>DIA</th> <th>TYPE</th> <th>BEARS</th> <th>DIST</th> <th>FACE/MARKINGS</th> </tr> </thead> <tbody> <tr> <td>36"</td> <td>Fir High Stump</td> <td>(N 59° E)</td> <td>(18.4 FT)</td> <td>Part.Healed Single Blaze Scribe Visible</td> </tr> <tr> <td>25"</td> <td>Fir</td> <td>(S 56° W)</td> <td>(46.8 FT)</td> <td>Healed Blaze</td> </tr> <tr> <td>26"</td> <td>Cedar</td> <td>(S 24° E)</td> <td>(35.0 FT)</td> <td>Healed Blaze</td> </tr> <tr> <td>13"</td> <td>Fir</td> <td>(N 48° E)</td> <td>(28.0 FT)</td> <td>Healed Double Blaze</td> </tr> <tr> <td>1/2"</td> <td>Iron Pipe</td> <td>West</td> <td>.5 FT</td> <td>Projecting 14"</td> </tr> <tr> <td>(18")</td> <td>(D. Fir)</td> <td>(N 21° W)</td> <td>(29.5 FT.)</td> <td>Not Searched For, Per map B-1048</td> </tr> </tbody> </table> <p>( ) = Record Measurement PER map B-1046</p>	DIA	TYPE	BEARS	DIST	FACE/MARKINGS	36"	Fir High Stump	(N 59° E)	(18.4 FT)	Part.Healed Single Blaze Scribe Visible	25"	Fir	(S 56° W)	(46.8 FT)	Healed Blaze	26"	Cedar	(S 24° E)	(35.0 FT)	Healed Blaze	13"	Fir	(N 48° E)	(28.0 FT)	Healed Double Blaze	1/2"	Iron Pipe	West	.5 FT	Projecting 14"	(18")	(D. Fir)	(N 21° W)	(29.5 FT.)	Not Searched For, Per map B-1048
DIA	TYPE	BEARS	DIST	FACE/MARKINGS																																
36"	Fir High Stump	(N 59° E)	(18.4 FT)	Part.Healed Single Blaze Scribe Visible																																
25"	Fir	(S 56° W)	(46.8 FT)	Healed Blaze																																
26"	Cedar	(S 24° E)	(35.0 FT)	Healed Blaze																																
13"	Fir	(N 48° E)	(28.0 FT)	Healed Double Blaze																																
1/2"	Iron Pipe	West	.5 FT	Projecting 14"																																
(18")	(D. Fir)	(N 21° W)	(29.5 FT.)	Not Searched For, Per map B-1048																																
<p><b>PLANE COORDINATE POSITION DATA</b></p> <p>State _____ Zone _____          North _____          West _____          Estab. By _____</p>	<p><b>DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER</b></p> <p>Corner is on the E-W CUTTING line on a west facing slope,          250 FT FROM the top of a N-S ridge. SW from the end of          Rd.# 1034120.          From Farmer Creek Road follow ridge just west of 4x4 post at road near home          follow ridge northerly to cutting line, walk east to corner just before draw</p>																																			

Signature \_\_\_\_\_ Title \_\_\_\_\_ Division \_\_\_\_\_ Headquarters \_\_\_\_\_ Date 7100-52 (3/68)

CORNER RECORD (PERPETUATION)

<p><b>MONUMENT : DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT</b></p> <p>Cleared brush around corner, painted bearing trees, replace/maintained signs          Maintained Line East 3/8 Mile &amp; West 1/4 Mile Blazed and Posted to standard</p>	<p>REGISTERED          PROFESSIONAL          LAND SURVEYOR</p> <p><i>John Ransom</i></p> <p>OREGON          JULY 21, 1992          JOHN C. RANSOM          2561</p>
<p><b>ACCESSORIES : DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE</b></p> <p>Marked          16" Fir Bears N 75° W 20.4 FT Scribed "T3SR10WS35""BT" on Double Blaze with 3/4" Brass Washer "LS2561"</p>	
<p>DONE BY: <u>Jonathan Drew</u> TITLE <u>LSIT</u> DATE <u>FY 2012</u> PLS NO./AGENCY/STATE _____          Certified Cor. Record Prepared? <u>Yes</u> Filed At: <u>TILLAMOOK COUNTY</u> DATE _____</p>	
<p><b>REMARKS</b></p> <p>Find rotten remains, (Fir S15E 42.1'), (Fir S50W 37.9'), (Fir N53W 80.9'), (Fir N33W 108.5'), (Fir N21W 29.5')          MEASUREMENTS TO ACCESSORIES MADE WITH STAFF COMPASS(15-1/2° DEC) AND STEEL TAPE</p>	

Index File No Z-21 T. 3S. & 4S. R. 10 W. Merid. W.M. Cor. SEC

