



CORNER INVESTIGATION REPORT

FS INDEX ID: X-25 & X-1

CORNER: 1/4 GCDB ID: 700140 & 100140 DATE: 6/11/2018
 TOWNSHIP: 3S STATE: OREGON
 RANGE: 8W & 7W COUNTY: TILLAMOOK
 SECTION: 36 & 31 FOREST: SIUSLAW
 MERIDIAN: WILLAMETTE DISTRICT: HEBO
 NFSL PROPERTY BOUNDARY CORNER?: YES NO
 LINE(S) POSTED: NORTH - 1985 SOUTH - 1985
 MAINTAINED: NORTH - 2017 SOUTH - NONE
 GUARD POST(S): NORTH - 3.0 FT SOUTH - 2.5 FT

HISTORY OF VISITATIONS:

- (1)1884 - H. MELDRUM, GLO SURVEY
- (2)???? - UNKNOWN SURVEYOR & YEAR
- (3)1962 - L. WHITMORE, USFS RECORD
- (4)1962 - L.M. ROSEBERRY, BLM RESURVEY, RW1/497 & 500
- (5)1967 - B. UDELL, CSF# A-1405
- (6)1969 - H. RUSSELL, CSF# B-598
- (7)1985 - L. BISHOP, CSF# B-1191

CORNER HISTORY:

- (1) ESTABLISHED CORNER, SET 16"x10"x8" BASALT STONE & 2 BT'S.
- (2) NO RECORD, LIKELY FOUND STONE & 2 BT'S, MARKS 2 NEW BT'S.
- (3) RECORD INDEX NOTES FOUND STONE & 4 BT'S.
- (4) FOUND STONE & 4 BT'S, SET IRON PIPE/BRASS CAP & 1 NEW BT.
- (5) FOUND "BRASS CAP (G.L.O)" & 2 BT'S.
- (6) FOUND US CADASTRAL PIPE & BRONZE CAP.
- (7) FOUND IRON PIPE/BRASS CAP & 4 BT'S, SETS ALUMINUM PIPE/CAP RM.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Jonathan B. Drew II

OREGON
DECEMBER 3, 2014
JONATHAN B. DREW II
89396

MONUMENT FOUND/SET:

FOUND A 2-1/2" GALVANIZED IRON PIPE WITH A 3-1/4" BRASS CAP, PROJECTING 2" ABOVE THE GROUND.

EXPIRES: 12/31/2019

RECORD MEASUREMENTS:

- (1,3)S28°E - 22.44 FT, (4)S24°E, (7)22.4 FT
- (1,3)S30°W - 23.1 FT, (4,7)S23°W
- (3)N83°W - 34.32 FT, (4)N84°W, (5)34.0 FT
- (3)EAST - 3.63 FT, (4)S83°E, (5)3.5 FT
- (4,7)N78°E - 115.5 FT
- (7)S64°37'E - 53.1 FT

RECORD CORNER ACCESSORIES:

- A 40" ROTTED FIR STUB WITH NO MARKS VISIBLE.
- ROTTED REMAINS OF AN INDETERMINATE SIZED FIR STUMP WITH NO MARKS VISIBLE.
- AN INDETERMINATE SIZE SAWN FIR STUMP WITH NO MARKS VISIBLE.
- A 13" ALDER WITH BARK SCRIBE VISIBLE.
- A 48" FIR WITH A HEALED DOUBLE BLAZE.
- A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR REFERENCE MONUMENT, PROJECTING 7" ABOVE THE GROUND. MARKED AS DESCRIBED IN (7).

METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN, FILED AS CONDITION REPORT.

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (7)S0°15'08"W - 2576.21 FT & (7)N0°15'26"W - 2650.06 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 15' 59.742"
 LONGITUDE: W 123° 36' 24.800"
 ELLIPSOID HEIGHT: ~1120 FT
 DATUM: WGS 84

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
 3106 PIERCE PARKWAY, STE D
 SPRINGFIELD, OREGON 97477

SOURCE: CONSUMER GRADE GPS, FOR NAVIGATION TO CORNER

DATE OF INVESTIGATION: 11/29/2017

REPORT BY: JONATHAN B. DREW II, PLS #89396, CFedS #1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH
 ANDREW HILLMAN, USFS SURVEY TECH

THIS DOCUMENT FILED IN CS OFFICE: YES
OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY FILED SEPARATELY

CAP DIAGRAM:

