



CORNER INVESTIGATION REPORT

FS INDEX ID: X-21

CORNER: 1/4 GCDB ID: 600140 DATE: 6/11/2018
TOWNSHIP: 3S STATE: OREGON
RANGE: 9W COUNTY: TILLAMOOK
SECTION: 35 & 36 FOREST: SIUSLAW
MERIDIAN: WILLAMETTE DISTRICT: HEBO
NFSL PROPERTY BOUNDARY CORNER?: YES NO
LINE(S) POSTED: SOUTH - 1984 NORTH - 1984
MAINTAINED: SOUTH - 2017 NORTH - NONE
GUARD POST(S): EAST - 3.0 FT
CORNER HISTORY:

HISTORY OF VISITATIONS:

- (1)1880 - S. CAUDLE, GLO SURVEY
- (2)1957 - L. ROSEBERRY, BLM RESURVEY & RW Bk1 Pg.498
- (3)1962 - L. WHITMORE, USFS RECORD
- (4)1984 - J. PROCHNAU, CSF# B-1173 & B-1176

NOTE: GUARD POST OFFSET FROM WC.

- (1) ESTABLISHED CORNER, MARKED 12" FIR FOR CORNER & 2 BT'S.
- (2) FOUND 47" FIR FOR CORNER & 2 BT'S, MARKS 2 NEW BT'S.
- (3) FOUND 47" FIR FOR CORNER TREE & 1 BT.
- (4) FOUND 52" FIR FOR CORNER & 3 BT'S, SETS ALUMINUM PIPE/CAP WITNESS CORNER & MARKS 2 NEW BT'S TO REFERENCE THE WITNESS CORNER.

MONUMENT FOUND/SET:

FOUND A 60" FIR FOR CORNER TREE WITH A HEALED BLAZE ON THE WEST SIDE.

RECORD CORNER ACCESSORIES:

NO TRACE FOUND OF A (1)5" BARBERRY, (2)DOWN/ROTTED 8" CASCARA
A 48" FIR WITH A HEALED SINGLE BLAZE.
A 48" FIR WITH A HEALED DOUBLE BLAZE.
A 36" FIR WITH A HEALED SINGLE BLAZE.
A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR WC, PROJECTING 3"
ABOVE THE GROUND AND MARKED AS DESCRIBED IN (4).
ACCESSORIES FOR THE WITNESS CORNER:
A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR WC, PROJECTING 1"
ABOVE THE GROUND AND MARKED AS DESCRIBED IN (4).
A 43" FIR WITH A HEALED FACE.

NEW CORNER ACCESSORIES:

NO NEW ACCESSOIRES ESTABLISHED.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (4)S2°11'28"W - 2651.81 FT & (4)N1°07'47"W - 2574.26 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 15' 57.149"
LONGITUDE: W 123° 44' 37.100"
ELLIPSOID HEIGHT: ~570 FT
DATUM: WGS 84

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
3106 PIERCE PARKWAY, STE D
SPRINGFIELD, OREGON 97477

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 12/13/2017

REPORT BY: JONATHAN B. DREW II, PLS #89396, CFedS #1664

FIELD CREW: ANDREW HILLMAN, USFS SURVEY TECH.
JORDEN REYES, USFS FIRE A.F.E.O.

THIS DOCUMENT FILED IN CS OFFICE: YES
OTHER DOCUMENT FILED WITH CS: NONE

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Jonathan B. Drew II

OREGON
DECEMBER 3, 2014
JONATHAN B. DREW II
89396

EXPIRES: 12/31/2019

RECORD MEASUREMENTS:

- (1)N17°W - 11.88 FT
- (1)S50°E - 13.2 FT. (2)S85°E - 10.56 FT & (4)N85°E - 10.2 FT
- (2&4)N66°E - 26.4 FT
- (2&4)S30°W - 50.82 FT
- (4)S53°W - 12.6 FT
- (4)S16°30'W - 43.8 FT FROM WC
- (4)S51°E - 30.9 FT FROM WC

METHOD OF MEASUREMENT:

NO NEW MEASURMENTS TAKEN,
FILED AS CONDITION REPORT.

CAP DIAGRAM:
PHOTO OF WC CAP:

