

**CORNER INVESTIGATION REPORT**

FS INDEX ID: N-23

CORNER: 1/4                      GCDB ID: 640400                      DATE: 5/2/2018  
TOWNSHIP: 3S                      STATE: OREGON  
RANGE: 8W                      COUNTY: TILLAMOOK  
SECTION: 13 & 24                      FOREST: SIUSLAW  
MERIDIAN: WILLAMETTE                      DISTRICT: HEBO

NFSL PROPERTY BOUNDARY CORNER?:  YES  NO

LINE(S) POSTED: SOUTH - 1986      WEST - 1980  
MAINTAINED: SOUTH - NONE      WEST - NONE  
GUARD POST(S): SOUTH - 34 FT                      EAST - 1.2 FT

CORNER HISTORY:

- (1) ESTABLISHED CORNER, SET POST & 2 BT'S.
- (2) NO RECORD. LIKELY FOUND 2 BT'S & SET WOODEN STAKE.
- (3) FOUND WOODEN STAKE, NOT ORIGINAL, & 2 BT'S, SET IRON PIPE/BRASS CAP & MARKED 2 NEW BT'S.
- (4) FOUND IRON PIPE/BRASS CAP & 2 BT'S.
- (5) NO RECORD, RECORD FOR NW CORNER S24 SAYS LINE POSTED EAST TO HERE.
- (6) FOUND IRON PIPE/BRASS CAP & 2 BT'S, SET ALUMINUM PIPE/CAP FOR RM.
- (7) NO RECORD LOCATED, LIKELY COUNTY SURVEYOR REWITNESS LATE 1980'S, SET CONCRETE CASING AROUND MONUMENT.

MONUMENT FOUND/SET:

FOUND 2-1/2" BRASS CAP FLUSH IN AN 8" GALVANIZED STOVE PIPE CASING FILLED WITH CONCRETE PROJECTING 4" ABOVE THE GROUND. NOTE: CAP MISSING YEAR MARKINGS "60", SEE PHOTO.

RECORD CORNER ACCESSORIES:

- A 40" ROTTED FIR SNAG BEARS, N60°30'E - 21.2 FT, WITH AX WORK VISIBLE.
- A ROTTED LOW CUT FIR STUMP BEARS, S25°E - 28.1 FT, WITH NO MARKS VISIBLE.
- A 34" FIR BEARS, N17°45'E - 4.3 FT, WITH A HEALED SINGLE BLAZE.
- A 30" FIR BEARS, S33°W - 22.4 FT, WITH A HEALED SINGLE BLAZE.
- A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR RM BEARS, N89°15'26"E - 43.92 FT, BURIED 2" BELOW GROUND LEVEL & MARKED AS DESCRIBED IN (6).

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ADDED

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREST HEIGHT.

NFSL LINES BEAR: S0°07'28"W - 1288.29 FT & S89°11'36"W - 2538.38 FT

GEODETTIC COORDINATES:

LATITUDE: N 45° 18' 07.38260"  
 LONGITUDE: W 123° 37' 00.52342"  
 ELLIPSOID HEIGHT: -1907 FT

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST  
 3106 PIERCE PARKWAY, STE D  
 SPRINGFIELD, OREGON 97477

DATUM: NAD83(2011), EPOCH:2010.0000

SOURCE: CONSTRAINED LEAST SQUARES NETWORK ADJUSTMENT, SEE MAP.

DATE OF INVESTIGATION: 1/13/2018

REPORT BY: JONATHAN B. DREW II, PLS# 89396, CFedS# 1664

FIELD CREW: JONATHAN B. DREW II, PLS#89396, CFedS# 1664  
 MICHAEL HUCK, BLM SURVEY TECH  
 ANDREW HILLMAN, USFS SURVEY TECH

HISTORY OF VISITATIONS:

- (1)1884 - H. MELDRUM, GLO SURVEY
- (2)???? - UNKNOWN SURVEYOR & YEAR
- (3)1960 - L.M. ROSEBERRY, BLM RESURVEY, CSF# A-859
- (4)1971 - L. WHITMORE, USFS RECORD
- (5)1980 - F. JOHNSON, USFS RECORD
- (6)1986 - J. GAHLSDORF, CSF# B-1215
- (7)???? - UNKNOWN SURVEYOR & YEAR, LIKELY CO. SURVEYORS OFFICE

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

*Jonathan B. Drew II*

OREGON  
 DECEMBER 3, 2014  
 JONATHAN B. DREW II  
 89396

EXPIRES: 12/31/2019

RECORD MEASUREMENTS:

- (1)N66°E - 19.14 FT, (3)N62°E - 21.12 FT
- (1)S28°E - 28.38 FT, (3)S25°30'E - 29.37 FT
- (3)N19°E - 4.62 FT, (4,6)4.6 FT
- (3)S34°W - 22.44 FT, (4,6)22.4 FT
- (6)N89°14'08"E - 43.87 FT

METHOD OF MEASUREMENT:

TRIMBLE S7 TOTAL STATION, SEE RECORD OF SURVEY FOR BASIS OF BEARINGS & OTHER INFORMATION.

BT BEARINGS TO CENTER, DISTANCES TO AN ALUMINUM NAIL SET AT SIDE CENTER.

CAP DIAGRAM:



THIS DOCUMENT FILED IN CS OFFICE: YES  
OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY

