

CORNER INVESTIGATION REPORT

FS INDEX ID: 0-21

CORNER: NORTH 1/16 GCDB ID: 600360 DATE: 5/11/2018

TOWNSHIP: 4S STATE: OREGON

RANGE: 10W COUNTY: TILLAMOOK

SECTION: 23 & 24 FOREST: SIUSLAW

MERIDIAN: WILLAMETTE DISTRICT: HEBO

NFSL PROPERTY BOUNDARY CORNER?: YES NO

LINE(S) POSTED: SOUTH - 1981 EAST - 1981

MAINTAINED: SOUTH - 2018 EAST - NONE

GUARD POST(S): SOUTH - 3.5 FT EAST - 3 FT

CORNER HISTORY:

(1) ESTABLISHED CORNER, SET ALUMINUM PIPE/CAP & 2 BT'S.

HISTORY OF VISITATIONS:

(1)1981 - J.S. PETERSON, CSF# B-987

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Jonathan B. Drew II

OREGON
DECEMBER 3, 2014
JONATHAN B. DREW II
89396

EXPIRES: 12/31/2019

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, PROJECTING 5" ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

A 37" CEDAR WITH A HEALED DOUBLE BLAZE.

A 16" ALDER WITH BARK SCIBING VISIBLE.

RECORD MEASUREMENTS:

(1)S70°E - 29.1 FT

(1)N73°W - 34.6 FT

NEW CORNER ACCESSORIES:

NO NEW ACCESSOIRES ESTABLISHED.

METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN, FILED AS CONDITION REPORT.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREST HEIGHT.

NFSL LINES BEAR: (1)S89°20'30"W - 2589.80 FT & (1)S0°05'29"W - 1311.68 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 12' 42.016"

LONGITUDE: W 123° 51' 55.579"

ELLIPSOID HEIGHT:

DATUM: WGS84

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 02/12/2018

REPORT BY: JONATHAN B. DREW II, PLS#89396, CFedS#1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH.

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
3106 PIERCE PARKWAY, STE D
SPRINGFIELD, OREGON 97477

CAP DIAGRAM:



THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: NONE

