

CORNER INVESTIGATION REPORT

FS INDEX ID: M-21

CORNER: SOUTH 1/16 GCDB ID: 600420 DATE: 01/04/2018
TOWNSHIP: 3S STATE: OREGON
RANGE: 10W COUNTY: TILLAMOOK
SECTION: 13 & 14 FOREST: SIUSLAW
MERIDIAN: WILLAMETTE DISTRICT: HEBO
NFSL PROPERTY BOUNDARY CORNER?: YES NO
LINE(S) POSTED: WEST - 1982 SOUTH - 1982
MAINTAINED: WEST - 2017 SOUTH - 2017
GUARD POST(S): WEST ~ 3 FT SOUTH ~ 6 FT
CORNER HISTORY:

HISTORY OF VISITATIONS:

(1)1982 - L.D. BISHOP, CSF# B-1085

(1) ESTABLISHED CORNER, SET ALUMINUM PIPE/CAP & 2 BT'S.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Jonathan B. Drew II

OREGON
DECEMBER 3, 2014
JONATHAN B. DREW II
89396

EXPIRES: 12/31/2019

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, PROJECTING 6" ABOVE THE GROUND.

RECORD MEASUREMENTS:

RECORD CORNER ACCESSORIES:

A 13" HEMLOCK WITH A HEALED SINGLE BLAZE.
A 18" HEMLOCK WITH A HELAED SINGLE BLAZE.

(1)N80°E - 15.7 FT
(1)N62°W - 21.2 FT

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.


METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN,
FILED AS CONDITION REPORT.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

CAP DIAGRAM:



NFSL LINES BEAR: (1)N86°38'35"E - 2687.35 FT & (1)N0°06'36"W - 1312.01 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 18' 21.970"
LONGITUDE: W 123° 51' 48.605"
ELLIPSOID HEIGHT:
DATUM: WGS 84

DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST
3106 PIERCE PARKWAY, STE D
SPRINGFIELD, OREGON 97477

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 12/06/2017

REPORT BY: JONATHAN B. DREW II, PLS#89396, CFedS#1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH.
KYRK BARRON, USFS FIRE F.E.O.

THIS DOCUMENT FILED IN CS OFFICE: YES
OTHER DOCUMENT FILED WITH CS: NONE

