## CORNER INVESTIGATION REPORT

FS INDEX ID: E-20

EAST 1/16 CORNER:

GCDB ID: 560600

DATE: 12/3/2019

**HISTORY OF VISITATIONS:** 

(1) 1991 - L. BISHOP, CS# B-1510

TOWNSHIP: 3 S RANGE:

**OREGON** STATE:

☑YES □NO

**COUNTY:** TILLAMOOK FOREST: SIUSLAW SECTION: 2 & 11

MERIDIAN: WILLAMETTE

NFSL PROPERTY BOUNDARY CORNER?:

**DISTRICT:** HEBO

LINE(S) POSTED: NORTH - 1991

NORTH - 2019

WEST - 1991

**MAINTAINED:** GUARD POST(S): NORTH - 1.4 FT WEST - 1.4 FT

**WEST-NONE** 

**CORNER HISTORY:** 

(1) ESTABLISHED CORNER BY SURVEY, SET ALUMINUM PIPE/CAP WITH 2 BT'S.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON JONATHAN B. DREW II

EXPIRES: 6/30/2021 **RECORD MEASUREMENTS:** 

(1)N39°30'W - 29.6 FT

(1)S51°15'W - 27.7 FT

### **MONUMENT FOUND/SET:**

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/2" ALUMINUM CAP, PROJECTING 4 INCHES ABOVE THE GROUND.

#### RECORD CORNER ACCESSORIES:

A 16" HEMLOCK WITH A HEALED DOUBLE BLAZE.

A 24" HEMLOCK WITH A HEALED DOUBLE BLAZE.

### **NEW CORNER ACCESSORIES:**

NO NEW ACCESSORIES ADDED.

METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN,

FILED AS CONDITION REPORT.

# CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S. BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (1)N1°15'49"E - 1344.98 FT & (1)N88°33'17"W - 1383.65 FT

GEODETIC COORDINATES:

**DOCUMENTS ON FILE AT:** 

LATITUDE: N 45° 19' 49.158" LONGITUDE: W 123° 44' 51.817"

WILLAMETTE NATIONAL FOREST 3106 PIERCE PARKWAY, STE D SPRINGFIELD, OREGON 97477

ELLIPSOID HEIGHT: ~ 925 FT

DATUM: WGS 84

SOURCE: CONSUMER GRADE GPS, FOR NAVIGATION TO THE CORNER.

DATE OF INVESTIGATION: 6/5/2019

REPORT BY: JONATHAN B. DREW II, PLS# 89396

ASSISTED BY: ANDREW HILLMAN, USFS SURVEY TECH

THIS DOCUMENT FILED IN CS OFFICE: YES CHRISTIAN HUNTER, USFS SURVEYOR TRAINEE OTHER DOCUMENT FILED WITH CS: NONE

**CAP DIAGRAM:** ORES

167