

2.5
3.6

TILLAMOOK COUNTY REWITNESS #90
 N. 1/4 36 SEC. 25 36 T 2N R 10 W., WM.
 COR. S. 1/4 25

HISTORICAL: Corner was set by PAROL
 Affidavit of HAROLD S. WILLIAMS. Corner was
 physically set by W.A. Markham R.E. #1842. Refer
 to Book 1 Page 186 during the year 1952. For the
 corner set a axle drive shaft. Made two bearing trees
 as follows; Spruce 14" bears South 20°
 Hemlock 24" bears N 14 1/2° W 48 7/2

CONDITION

FOUND:

Found an axle in old turn-out area and found both bearing trees made by
 W.A. MARKHAM as described in Book 1 Page 186. Found Blazed line made
 by J.L.C. (R.S. 287) in 1965 -- refer to MAP A-1214. The blazed line bears
 N 1° 25' 46" E from corner. Centerline (apparent) is ± 25 North of
 corner.

COMMENTS: MAP B-565 MAP B-389
 MAP A-1208

REWITNESS

I SET 2" Iron Pipe with Brass Cap in Concrete and tile in place of axle
 N feet

36 " Hat Section North 393

1 - 25
4 - 36
RS287
1972

NEW ACCESSORY: I used blazed line shown on map A-1214
 as a meridian (N 1° 25' 46" E). Found b.t. by W.A. Markham.
 This tree I blaze on face and place yellow with spike in
 blaze. I turn angle to spike and chain to spike which
 is as follows; 36" Hemlock (Top of bank northside of
 graveled road) bears N 13° 37' W 48 4/4 feet. Found other
 b.t. by W.A. Markham did the same as described above with
 spike and yellow tag. I found the following; 24" Spruce bears S 11° E 19 2/2 feet.
 I make new Bearing tree with spike and yellow tag as follows: 37" Double
 spruce bears S 85° 44' W 53 5/4 feet to spike in face which is scribed 536
 BT CS

IN THE PRESENCE OF:

Geo Urrey
 Gale Arthur
 Jim Boehm

DATE: June 1972

PHOTO#:

County corner tag affixed.

TITLE