

Index File No. _____ T <u>3 S</u> R. <u>7 W</u> R.D. _____ Merid. <u>WILL.</u> N.F. _____ State <u>OREGON</u>	CORNER RECORD (SEARCH) (Ref. FSM 7151.4)	Tract or Survey No. <u>#475</u> Cor. No. _____
CORNER DIAGRAM 	DESCRIBE CORNER MONUMENT FOUND <u>GLO 1873 SET 14X8X6 STONE.</u> <u>WEST 2.60 CHAINS A BROCK, 10 LKS. WIDE, RUNNING SOUTH.</u> <u>NO WITNESS TREES.</u>	
PHOTO IDENTIFICATION DATA Photo No. _____ Filed At. _____ Object Ident. _____ Ident. By _____ Signature _____	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND <u>FOUND 17X11X7 STONE WITH 3 NOTCHES ON EAST AND SOUTH EDGES.</u>	
PLANE COORDINATE POSITION DATA State _____ Zone _____ X _____ Y _____ Estab. By _____ Agency _____	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER <u>See OTHER SIDE</u>	

CORNER RECORD (PERPETUATION)	
MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT. <u>SET 1 1/2" IRON PIPE ON SOUTH EDGE OF ORIGINAL STONE.</u> <u>SET IRON FENCE POST ON NORTH SIDE OF STONE WITH BLM SURVEY MARKER SIGN ATTACHED.</u>	
ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE <u>SCRIBED A 29" FIR, N. 50° E., 13 1/2 FT. TO NAIL HEAD AT SCRIBED "B"</u> <u>SCRIBED T3SR7W S14 BT'S.</u> <u>SCRIBED A 24" FIR, S. 29° 30' W., 16 1/2 FT. TO NAIL HEAD AT SCRIBED "B"</u> <u>SCRIBED T3SR7W S22 BT'S.</u>	
By <u>Leonard Whitmore, Tillamook County Deputy Surveyor</u> Date <u>5-22-71</u>	
Work Done By <u>Leonard Whitmore</u> Title <u>Deputy Surveyor</u> Date _____	State Registration No. _____ or Agency _____
Certified Cor. Record Prepared? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Filed At <u>Tillamook County Courthouse</u> Date <u>6-71</u>
REMARKS <u>WITNESSES: GARRY WHITMORE } BLM</u> <u>JIM LARREW }</u> <u>DARYL WHITMORE }</u>	