

T 4 R 9 W No. N 2 / Cor. Mer. Will State (Oregon) N.F. Dist. H 4 4 0

3. Original Description Vol. Page Where Recorded

4. Description of Corners: **#694**
 Fir post with rock mound.

5. Investigation Notes:
 Find 48 in. snag S. 67 1/2° W., 31 ft. with visible scribing BT
 Find 48 in. snag N. 36 1/2° W., 36 ft. with visible but not legible scribe marks.
 Other two BTs are in their correct positions by bearing and distance but all scribing is rotted off.
 Find rock mound at exact point for corner placed by original surveyor.

6. Signed L. Whitmore Title Surveyor Date 1-7-61

Corner Status

1-4	1-3
2-3	2-4

Photo Identification
 Photo No. _____
 Ident. By: _____

Plane Coordinate Position Data
 State _____ Zone _____
 X _____
 Y _____

Estab. By _____
 Field Book No. _____
 Where Filed _____

Evaluation
 Authentic _____
 Needs Verif. Monument
 Re-estab. Survey _____
 and Status N.F.

PERPETUATION RECORD

Monument: Original rock mound

Accessories: new BTs
 13 in. fir S. 62° W., 13 ft. scribed T4SR9W S 23 BT
 13 in. fir N. 8° W., 24 ft. scribed T4SR9W S 14 BT
 13 in. fir N. 54° E., 42 ft. scribed T4SR9W S 13 BT
 13 in. fir S. 58° E., 23 ft. scribed T4SR9W S 24 BT

12. Set By _____ Title _____
 License _____ Agency _____ Date _____

13. Recorded By _____ (Agency) _____ Volume _____ Page _____
 (Date) _____ (City) _____ (County) _____ (State) _____

Remarks:
 Scribing by deputy surveyor M. Whitmore
 witnessed by L. Whitmore