

CORNER RECORD (SEARCH) (Ref. FSM 7151.4) Tract or Survey No. Cor. No.

Index File No. T-9 R.D. HEBO County TILLAMOOK State ORE.

T. 5 S R. 10 W Merid. WILL. N.F. SUSLAW

CORNER DIAGRAM

DESCRIBE CORNER MONUMENT FOUND GLC 1882 SET POST & MARKED
10" ALDER, S. 76° E., 28 LKS.
8" SPRUCE, S. 14° W., 15 LKS. #913

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
WM MARKHAM ORLS # 1842 PROPORTIONED A 1/4 CORNER
IN 1951 AND MARKED 2 WITNESSES; He SET 1 1/2" IRON PIPE.
22" SPRUCE, N. 48° W., 9 1/2 FT.
16" SPRUCE, S. 69° E., 9 3/4 FT.

PHOTO IDENTIFICATION DATA
 Photo No. ETJ-5-154
 Filed At.
 Object Ident. DIRECT
 Ident. By L. Whitmore Signature

PLANE COORDINATE POSITION DATA
 State Zone
 X
 Y
 Estab. By Agency

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
FOUND 1 1/2" BENT IRON PIPE.
FOUND 16" DECAYED SPRUCE STUB, S. 69° E., 9 3/4 FT. WITH
MARKS WEATHERED OFF.
THE N.W. BT IS AN UPROOTED STUMP.
PAINT RED BAND AROUND S.E. STUB.

Signature Leonard Whitmore Title Forestry Tech Div. Timber Headquarters Hebo Date 2-24-71 7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

Work Done By Title Date State Registration No. or Agency

Certified Cor. Record Prepared? Yes No Filed At: Date

REMARKS
I REFERENCE 60" SNAG, S. 20° W., 11 1/2 FT. WITH LOCATION POSTER
FOLLOW PUBLISHERS PAPER CO. SQUAW CR. ROAD AT ROAD JUNCTION
FOLLOW RED AND BLUE RIBBON LINE WEST 100 FT. TO CORNER.
Leonard Whitmore, USFS, 2-24-71

Index File No. T. 5 S R. 10 W M. Tract or Surv. No. 1/4 Cor. 28-29