

Asbestos Disposal Requirements

First, determine if your materials require an **Asbestos Survey**

- Asbestos Surveys are not required for waste loads solely comprised of mastics and roofing products that are fully encapsulated with a petroleum-based binder and are not hard, dry, or brittle, and are not made friable. This material is considered exempt from ACM packaging/disposal requirements.
- A Survey is required for loads containing demolition, renovation and/or roofing material that is not fully encapsulated if the load is from either of the following:
 - A public or private commercial building.
 - A residential unit prior to any demolition.
 - All loads of construction and demolition debris are required to complete a C& D form.

If your materials require an Asbestos Survey, you must arrange testing by an accredited testing lab.

- The survey must contain the address of the point-of-generation.
- If the survey states the load does not include Asbestos Containing Material (ACM), the load can be accepted as non-ACM.
- If the survey states the load contains ACM, the load must meet DEQ asbestos waste materials disposal requirements.

Professional Asbestos Abatement Contractors are trained in the proper methods to remove asbestos from your home or other structure. A list of licensed asbestos abatement contractors can be found at www.oregon.gov/deq/FilterDocs/asb-contr.pdf.

ACM is any material containing more than 1% asbestos by weight. The Oregon Department of Environmental Quality (DEQ) regulates the disposal of ACM from public and private buildings to prevent asbestos fiber release and exposure.

ACM Disposal Requirements

The Tillamook Transfer Station is able to accept small quantities of properly prepared ACM from residents, according to the following guidelines:

1. Plan for Your Disposal

- Tillamook County provides for small quantities of ACM disposal by appointment only. Call the Tillamook Transfer Station at (503) 842-4588 to schedule an appointment.

2. Wet, Wrap and Label Your Load

- Wet ACM thoroughly with water to ensure it remains wet until disposal.
- Place friable and non-friable ACM in leak-tight containers such as two 6-mil asbestos disposal bags for a minimum thickness of 12-mil. Fiber, plastic, and steel drums are also acceptable containers, as long as all drums are lined with one 6-mil plastic asbestos disposal bag inside to quality as two bags, and the drum lids are sealed with duct tape or equivalent.
- Each 33 x 50, 6 mil. Asbestos defined bag may contain a maximum of 25 pounds of ACM.
- Label ACM packaging as required. (See back panel).

3. Complete an Asbestos Waste Shipment Report

- An Asbestos Waste Shipment Report (ASN-4) is required for each ACM load.
- Forms are available at the transfer station office, DEQ website or at the Solid Waste website at www.co.tillamook.or.us/gov/solidwaste.
- Our staff will review all forms for accuracy and completeness. We will also inspect waste loads to verify accuracy of form information.

ACM that is improperly packaged or labeled will not be accepted. No exceptions.

Note: If there is an issue with the packaging tearing or rupturing, the customer/and or generator may be responsible for clean-up fees and any costs imposed on the facility.

Tillamook County is required to share ASN-4 reports and other information with DEQ. The provision of this service does not exempt homeowners or contractors from other requirements. Tillamook County does not assume

any responsibility for the actions taken by homeowners or contractors in their compliance with DEQ or other regulations or requirements.

ACM Must Be Labeled with the following information:

- ✦ Danger
- ✦ Contains Asbestos Fibers
- ✦ Avoid Creating Dust
- ✦ Cancer and Lung Disease Hazard
- ✦ Avoid Breathing Airborne Asbestos Fibers
- ✦ Name of ACM generator
- ✦ Location where ACM was generated

Hours & Pricing

- Tillamook Transfer Station accepts friable and non-friable ACM **by appointment only** 8 a.m. – 2 p.m., Monday – Friday. Call the Tillamook Transfer Station at **(503) 842-2431** to schedule an appointment.

Disposal Pricing:

- Bagged material: \$10.00 per bag (maximum 25 lbs., max 38 x 60)
- Sealed Drums: \$0.16 per pound (maximum 55 gal.)
- Other: \$319.75 per ton (minimum \$10.00)

Final Checklist for ACM Disposal

- ✓ Wet, wrap and label your load
- ✓ Complete a Waste Shipment Report (ODEQ issued ASN-4 Form)
- ✓ Bring extra packaging supplies in case of damage during transport

Tillamook Transfer Station offers the following Asbestos Packaging Material:

- Asbestos bags: \$2.50 per bag
- Duct tape: \$10.00 per roll
- Labels: \$0.30 per label